

EnviroSense2 (E2) Environmental Sensor Module, Temperature, TAA

MODEL NUMBER: E2MT



Monitors ambient temperature conditions.

Description

The E2MT E2 Environmental Sensor Module works with LX Platform devices, including WEBCARDLX, WEBCARDLXE, WEBCARDLXS, PDU3XE-Series PDUs and PDU3E-Series PDUs. By connecting the included USB cable to an LX Platform device, the E2MT allows you to remotely monitor ambient temperature conditions in network environments.

If temperature values exceed a certain limit, it is recorded in the event log of the LX Platform device's PowerAlert® Device Manager interface. The E2MT mounts magnetically to most racks and cabinets. Up to three E2 modules can be daisy-chained together. A built-in retention harness secures cable connections to reduce clutter.

Features

Compatible with LX Platform Devices Compatible devices include WEBCARDLX, WEBCARDLXE, WEBCARDLXS, PDU3XE-Series PDUs and PDU3E-Series PDUs Measures and monitors ambient temperature

Easy to Install and Operate Attaches magnetically to most racks and cabinets Up to 3 E2 modules can be daisy-chained together Built-in cable harness reduces clutter USB cable included Compatible with free downloadable PowerAlert software

Highlights

- Compatible with LX Platform devices
- Easy magnetic mounting to most racks and cabinets
- Up to 3 E2 modules can be daisy-chained together
- Built-in cable harness reduces clutter
- USB cable included

Package Includes

- E2MT EnviroSense2 Environmental Sensor Module
- USB cable (A to Micro-B), 3 ft.
- Owner's manual

Specifications

OVERVIEW	
UPC Code	037332196293
CONNECTIONS	
Side A - Connector 1	USB A (FEMALE)
Side B - Connector 1	MICRO-USB B (FEMALE)
PHYSICAL	



Powering Business Worldwide

TRIPP LITE
SERIES

Cable Length (ft.)	3
Cable Length (m)	0.91
Shipping Dimensions (hwd / in.)	1.10 x 4.20 x 5.90
Shipping Dimensions (hwd / cm)	2.79 x 10.67 x 14.99
Shipping Weight (lbs.)	0.28
Shipping Weight (kg)	0.13
Unit Dimensions (hwd / in.)	0.830 x 2.520 x 1.420
COMMUNICATIONS	
Product Compatibility	WEBCARDLX; WEBCARDLXMINI; WEBCARDLXE
FEATURES & SPECIFICATIONS	
Sensing Capability	Temperature
Contact Closure Capability	Contact Closure Input Monitoring
STANDARDS & COMPLIANCE	
Product Compliance	Trade Agreements Act (TAA)
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	2-year limited warranty

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.