

**inSIGHT™ Data Com Rack Power Distribution Unit**  
**Intelligent Power Distribution**  
**Complete line of single and three phase**  
**intelligent PDUs**

# HUBBELL

## Features

- High reliability with robotically soldered connections
- Up to four environmental sensors per PDU that measures temperature and humidity
- Monitored and switch enabled - Use Switching cords for equipment switching capability.
- Available in Black, Blue, Red, and White



## Ordering Information

Type	Nominal	Catalog Number	UPC
Switch Ready	120V Single Phase	PV72IA20AA-6	662620364698

## Listings

UL 2416  
 EIA 310-E Universal Mounting Pattern  
 UL 60950-1  
 SNMP V3

## Specifications

Input Current (A)	20 Amp
Input Power Cord	L5-20P Plug
Receptacle group	24 L5-20R Receptacle
PDU Size	72" vertical mount
Regulatory Approval	TUV Certified to UL / CSA 609050-1
Operating Environment	0 to 60
Storage Environment	-25 to 65
PDU Dimension (inches)	72 length X 2.2 width X 4.8 depth
Network Interface	Dual Ethernet RJ-45, 10/100 Mbit/sec

## Performance

### Intelligence

Remote & touch screen display

### Low profile

2.18" X 2". Improves airflow

### Touch and Rotate Digital Display

Touch to view / rotate. Optional sensor -daisy chain up to four for temp/humidity

## Accessories

One Sensor (A) and 6 foot connecting cord	<b>PENVPODA</b>
Two Sensors (A, B) and two 6 foot connecting cord	<b>PENVPODAB</b>
Three Sensors (A, B, C) and three 6 foot connecting cords	<b>PENVPODABC</b>
Four sensors (A, B, C, D) and four 6 foot connecting cords	<b>PENVPODABCD</b>
Environmental sensor 6 foot connecting cord	<b>PENV6FTCORD</b>
Environmental sensor 9 foot connecting cord	<b>PENV9FOOTCORD</b>
Outlet Switching and Metering, C13-C14, 5 foot	<b>PSWCRDC1314-05</b>
Outlet Switching & Metering, C19-C20, 5 foot	<b>PSWCRDC1920-05</b>

