

**60995BS**

12/2 Stranded Unshielded FPLP

Fire Alarm Signaling

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	2
• AWG Size	12
• Conductor Stranding	7x20 Stranded
• Conductor Type	Bare Copper
• Nominal DCR	1.8 Ohm/1000ft
• Cabling Lay Length	4 in
• Twists/Foot	3 twist/ft
INSULATION PARAMETER	-
• Insulation Type	Plenum PVC
• Insulation Thickness	0.09 in
• Insulation Color Code	1. Black 2.Red
SHIELDING PARAMETER	-
• Shield Type	None
ELECTRICAL CHARACTERISTICS	-
• Nom. Cap. Between Conductors	40 pF/ft

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	Flexible Plenum
Jacket Thickness	0.015 in
Nominal Cable O.D.	0.239 in
Plenum	Yes
NEC UL Rating	FPLP
RoHS Compliant	Yes
Pull Tension	159 lbs
Bend Radius	2.151 in
Cable Weight	55 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	NFPA 262 Plenum
Operating Range	-0 to 60 Deg C
UL Voltage Rating	300

Detailed Specification & Technical Data



60995BS

12/ StrnadedUnshielded FPLP
Fire Alarm Signaling

Related Products

RELATED PRODUCTS	-
Non Plenum Number	998S
Aquaseal Direct Burial Number	AQ227