Product data sheet

Specifications



SmartUPS Industrial Battery 50Ah 12VDC Extended Temperature Shelf Mount

XB050XX1XS

Overview

Lead time	Usually in Stock

Main

Product or Component Type	Battery
Battery Type	Gel Cell
Range of Product	Smart-UPS Battery Systems

Batteries & Runtime

Battery blocks per string	4
Battery Slots Empty	0
Included Battery Modules	0
Device mounting	Stand alone battery stack
Battery Voltage	12 V

Physical

Height	8.07 in (20.5 cm)
Width	5.43 in (13.8 cm)
Depth	9.02 in (22.9 cm)
Product Weight	36.6 lb(US) (16.6 kg)
Mounting Mode	Not rack-mountable

Conformance

Product Certifications	UL Recognized
Marking	CE Mark

Environmental

Ambient air temperature for operation	-4…131 °F (-20…55 °C)
Ambient Air Temperature for Storage	-4…122 °F (-20…50 °C)

Ordering and shipping details

GTIN	731304327165

Packing Units

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.98 in (27.9 cm)
Package 1 Width	10.00 in (25.4 cm)
Package 1 Length	6.50 in (16.5 cm)
Package 1 Weight	38.008 lb(US) (17.24 kg)

Contractual warranty

Warranty	2 years repair or replace

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration

Use Again

Repack and remanufacture

Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	No