



NA3FJ

3 pole XLR female - Stereo 1/4" locking jack (tip, ring, sleeve contact)

Features & Benefits

- Versatile, pre-wired and ready to use adapters to reliably interlock various connector systems
- Professional look and compact space saving design, based on the XX Series
- Rugged diecast shell for best reliability

Technical Information

| Product | |
|-----------------|---------|
| Title | NA3FJ |
| Connection Type | Adapter |

| Electrical | |
|-----------------------|---------------------------------|
| Contact resistance | $\leq 3 \text{ m}\Omega$ (XLR) |
| Contact resistance | $\leq 6 \text{ m}\Omega$ |
| Dielectric strength | 1.5 kV dc / > 1 kVdc (XLR/Jack) |
| Insulation resistance | > 2 G Ω |

| Mechanical | |
|----------------|------------|
| Wiresize | |
| Locking device | Latch lock |

| Material | |
|-----------------|----------------------------|
| Contact plating | 2 μm Ag |
| Contacts | Bronze (CuBe2) (jack) |
| Insert | Polyamide (PA 6.6 30 % GR) |
| Shell | Zinc diecast (ZnAl4Cu1) |
| Shell plating | gal Cu/Ni |

| Environmental | |
|-------------------|------------------|
| Temperature range | -20 °C to +65 °C |