

# Product data sheet

Specifications



## Cable, UPS Communications Smart Signalling

940-0024

### Overview

|           |                  |
|-----------|------------------|
| Lead time | Usually in Stock |
|-----------|------------------|

### Main

|              |                  |
|--------------|------------------|
| Cable length | 6.56 ft (2.00 m) |
|--------------|------------------|

|                  |   |
|------------------|---|
| Number of cables | 1 |
|------------------|---|

|                       |     |
|-----------------------|-----|
| Product Compatibility | UPS |
|-----------------------|-----|

### Physical

|       |       |
|-------|-------|
| Color | Black |
|-------|-------|

|                |                       |
|----------------|-----------------------|
| Product Weight | 1.01 lb(US) (0.46 kg) |
|----------------|-----------------------|

|                   |       |
|-------------------|-------|
| Mounting Location | Front |
|-------------------|-------|

|               |                    |
|---------------|--------------------|
| Mounting Mode | Not rack-mountable |
|---------------|--------------------|

|             |                               |
|-------------|-------------------------------|
| Connector B | SUB-D 9 male Smart Signalling |
|-------------|-------------------------------|

|             |                                 |
|-------------|---------------------------------|
| Connector A | SUB-D 9 female Smart Signalling |
|-------------|---------------------------------|

### Output

|                |   |
|----------------|---|
| Number of port | 1 |
|----------------|---|

### Environmental

|                           |          |
|---------------------------|----------|
| Storage Relative Humidity | 0...95 % |
|---------------------------|----------|

|                  |  |
|------------------|--|
| Storage altitude | 0...50000 ft (0.0000000000...15240.0000000000 m) |
|------------------|--|

|                                       |                         |
|---------------------------------------|-------------------------|
| Ambient air temperature for operation | 32...113 °F (0...45 °C) |
|---------------------------------------|-------------------------|

|                   |          |
|-------------------|----------|
| Relative Humidity | 0...95 % |
|-------------------|----------|

|                    |              |
|--------------------|--------------|
| Operating altitude | 0...10000 ft |
|--------------------|--------------|

|                                     |                          |
|-------------------------------------|--------------------------|
| Ambient Air Temperature for Storage | 5...113 °F (-15...45 °C) |
|-------------------------------------|--------------------------|

### Ordering and shipping details

|      |              |
|------|--------------|
| GTIN | 731304316350 |
|------|--------------|

### Packing Units

|                        |     |
|------------------------|-----|
| Unit Type of Package 1 | PCE |
|------------------------|-----|

|                              |   |
|------------------------------|---|
| Number of Units in Package 1 | 1 |
|------------------------------|---|

|                  |                   |
|------------------|-------------------|
| Package 1 Height | 9.02 in (22.9 cm) |
|------------------|-------------------|

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

|                         |                       |
|-------------------------|-----------------------|
| <b>Package 1 Width</b>  | 2.01 in (5.1 cm)      |
| <b>Package 1 Length</b> | 4.02 in (10.2 cm)     |
| <b>Package 1 Weight</b> | 1.01 lb(US) (0.46 kg) |

---

## **Contractual warranty**

---

|                 |                           |
|-----------------|---------------------------|
| <b>Warranty</b> | 2 years repair or replace |
|-----------------|---------------------------|

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

|  <b>Materials and Substances</b> |   |
|---|---|
| Packaging made with recycled cardboard  | No  |
| Packaging without single use plastic  | No  |
| <a href="#">EU RoHS Directive</a>   | Compliant   |
| California proposition 65   | <b>WARNING:</b> This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |

### Use Again

|  <b>Repack and remanufacture</b> |  |
|---|--|
| Take-back   | No   |
| WEEE  |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |