



KCA2074

KCA2071/U + CA9212 + 3 x 6751W/U



The kit includes: 1 x art. CA2100P - CIAO wall-mounted entrance panel with facility for 1/2/4 buttons, 4 x art. 6751W/U - MINI hands-free door-entry phone complete with adapter plates art. 6754, 1 x art. CA9210 - 2 double-height buttons for CIAO entrance panel, 1 x art. CA9211 - 4 single buttons for CIAO entrance panel, 1 x art. CA9213 - 1 large button for CIAO entrance panel, 1 x art. CA9212 - 4 double buttons for Ciao entrance panel, 1 x art. 1209 - video kit power supply unit. Simplebus2 digital 2-wire system.



KCA2074

KCA2071/U + CA9212 + 3 x 6751W/U

PRODUCTS IN THE KIT



KCA2071/U CIAO-MINI HF ONE-FAMILY AUDIO KIT + 6754. S2

The kit includes: 1 x art. CA2100P - CIAO wall-mounted entrance panel with facility for 1/2/4 buttons, 1 x art. 6751W - MINI hands-free door-entry phone, 1 x art. 6754 - adapter plate for Mini hands-free audio door-entry phone, 1 x art. CA9210 - 2 double-height buttons for CIAO entrance panel, 1 x art. CA9211 - 4 single buttons for CIAO entrance panel, 1 x art. CA9213 - 1 large button for CIAO entrance panel, 1 x art. 1209 - video kit power supply unit. Simplebus2 digital 2-wire system.



KCA2074

KCA2071/U + CA9212 + 3 x 6751W/U



CA9212 4 DOUBLE BUTTONS FOR CIAO ENTRANCE PANEL

Double buttons for use with the Ciao series entrance panel.

GENERAL DATA	
Height (inch) (in)	0.56
Width (inch) (in)	1.91
Depth (inch) (in)	0.31
Product color	Transparent
Flush-mounted	Yes
COMPATIBLE SYSTEMS	
Audio Simplebus 2 with power supply art. 1210/1210A	Yes
Traditional	Yes
HARDWARE FEATURES	
Call type	Push-buttons
Type of buttons	Mechanical
Number of push-buttons (n°)	8
ENVIRONMENTAL AND COMPLIANCE FEATURES	
Operating temperature (°F)	-13 ÷ 131
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	III



KCA2074

KCA2071/U + CA9212 + 3 x 6751W/U



6754 ADAPTER PLATE FOR MINI HANDSFREE AUDIO

Adapter plate for hands-free Mini audio door-entry phone.

MAIN FEATURES	
Height (inch) (in)	6.18
Width (inch) (in)	6.18
Depth (inch) (in)	0.16
GENERAL DATA	
Type of finishing materials	PMMA
Product color	White RAL9003
MOUNTING/INSTALLATION	
Wall-mounted	Yes
AUDIO/VIDEO FEATURES	
Audio system	Yes



KCA2074

KCA2071/U + CA9212 + 3 x 6751W/U



6751W HANDS-FREE MINI DOOR-ENTRY PHONE. SIMPLEBUS2 (1210A)

Mini series door-entry phone with full-duplex audio. Allows loudspeaker volume control and ringtone volume control, with choice of different melodies. Equipped with 5 touch sensitive buttons for audio key, lock-release, actuator control, switchboard call and privacy function, with door status indicator LED. Manages floor door calls as standard. Complete with 2 x 8-position dip-switches for programming user code and buttons. Wall-mounted. The door-entry phone can be used in Simplebus2 audio systems with power supply art. 1210. Dimensions: 105x105x20 mm.

GENERAL DATA	
Height (inch) (in)	4.13
Width (inch) (in)	4.13
Depth (inch) (in)	0.79
Product color	White
Product weight (oz) (oz)	5.29
Wall-mounted	Yes
Audio/video system	Yes
ELECTRICAL CHARACTERISTICS	
Supply voltage	22÷35VDC
HARDWARE FEATURES	
Clamps	L L CFP1 CFP2
Removable terminals	Yes
Total buttons (n°)	5
LED signaling (no.) (n°)	3
ENVIRONMENTAL AND COMPLIANCE FEATURES	
Operating temperature (°F)	23 ÷ 104
Operating humidity (RH max) (%)	25 ÷ 75



KCA2074

KCA2071/U + CA9212 + 3 x 6751W/U

GENERAL FEATURES

Absorption during communication (mA)	130
Call to multiple addresses	Yes
Selective intercom call	Yes
Panic call	Yes
Doctor	Yes
Switchboard call function	Yes
Floor door call function	Yes
Actuator control function	Yes
Intercom function	Yes
Privacy function	Yes
Key button function	Yes
Hands-free function	Yes
Loudspeaker volume control	Yes
Ringtone volume control	Yes
Simplebus 2 audio system	Yes
Electronic bell	Yes
Customisable ringtone	Yes
Sensitive Touch technology	Yes