

Cat6 110-Style Wall Mount Patch Panel, 12-Port, 1RU

MANAGING AND ORGANISING COPPER ETHERNET NETWORK



Overview

The 12-port Cat6 patch panel with 110 punch down termination is color coded for both T568A and T568B wiring, providing the perfect solution for any voice or LAN application. The included 89D bracket offers a convenient wall-mount installation, especially in tight spaces. For hassle-free connections, this Ethernet patch panel offers straight Cat6 ports with 110 type termination, making it easy to insert and remove your cables. The clear numbering on the front and back of the network patch panel enables quick and easy identification of cable runs for efficient system management.

Benefits

- Snap-on 89D Brackets Helps Install and Manage Cables
- Easy to Mounted on a Flat Wall Surface or Desk
- Can Be Clearly Identified with Optional Labels and Icons for Port Identification
- Terminates 4-pair, 23–24 AWG, 100-ohm Twisted Pair Cable with T568A/B Schemes
- Support POE/POE+ /POE++ (IEEE 802.3af/at)
- Provides a Quick Plug and Play Connection to RJ45 Patch Cords, Backwards Compatible

Technical Specification

Characteristics	WC6P-U12P1101U
Electrical	
Current Rating	1.5AMP
Contact Resistance	100 milliohms max @ 500 VDC
Insulation Resistance	1000 megohms min
Insulation Strength	750 VAC RMS 60Hz,1min
Environment	
Storage Temperature	-40 to 70°C (-40 to 158°F)
Operating Temperature	-20 to 60°C (-4 to 140°F)
Mechanical	
IDC Housing Material	PBT
Panel Frame Material	SPCC, black or industrial grey electrostatic powder coating
Rj45 Jack Life	750 times min
IDC Life	200 times min
Contact Material	Phosphor bronze stamp pin T=0.30mm
IDC Contact Material	Phosphor bronze nickel plating
Wire	AWG 23-24
Dimensions(HxWxD)	1.65"x10.06"x2.26" (42x255.5x57.5mm)

Product Specification

Unit:mm

