



### EPS156 Code Call (Code Blue) Station (Non-Supervised) (AlphaLinQ™ 100 series)



#### ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The Code Call / Code Blue Push/Pull Stations shall be shall be Alpha Communications® AlphaLinQ™ 100 series model **EPS156**, or approved equal. Operation of emergency signals shall be accomplished by a short pull on the (optional model **CA015K** nylon cord or **CA016K** TPU plastic cord) or by pulling / pushing down on the Blue lever marked 'CODE'.

The Red "CALL PLACED" L.E.D. indicator shall flash to assure the patient that the call has been placed. Switching mechanism shall consist of a reliable DPDT switch. The **EPS156** shall be used in conjunction with a **AC153** third priority control unit, to provide a separate and distinct flash and tone rate. **The EPS156 is not a 'supervised' code call station.**

The Red "CALL PLACED" L.E.D. indicator shall flash to assure the patient that the call has been placed. Switching mechanism shall consist of a reliable DPDT switch.

The **EPS156** is not designed to be used in wet or damp environments.

All electronic components needed for these features shall be mounted on a printed circuit board and all station components shall be mounted on a rugged ABS plastic faceplate. The station(s) shall be installed in a single gang ring with square box. Plug-in connectors shall be provided for connections. The **EPS156** shall be UL® 1069 Listed to the latest standards.

Contractor shall observe all local and national electrical and building codes.

#### EPS156 CODE CALL (CODE BLUE) STATION (NON-SUPERVISED)

The Alpha Communications® **EPS156** Code Call / Code Blue Station may be used to operate all system code signals (except 'supervised' code blue applications). It may be used independently or connected with other call stations or intercom stations. All electronic components are mounted on a circuit board. The **EPS156** features a built-in Red (flashing) LED.

Due to the flexibility of its design, it may be used as a PULL CORD CODE STATION, or a PUSH TYPE CODE CALL STATION. The optional (model **CA015K** or **CA016K**) pull cord may be used for emergency pull activation, or if so desired, the standard LARGE BLUE push/pull down lever may be used.

The **EPS156** is used primarily with the AlphaLinQ™ 100 series visual nurse-call system, but can be used and is backwards compatible with some older systems as well. The **EPS156** is U.L. 1069 listed, to the latest standards.

#### FEATURES

- U.L. Listed 1069 - to the latest standards
- Simple and flexible operation.
- RED L.E.D. "Called Placed" indicator (flashing)
- Call cancel only at point of origin.
- Flame Retardant type ABS White Plastic Faceplate
- Can be used as a Pull or Push type station
- Corridor Zone Light Capability (optional)

#### SPECIFICATIONS

<b>Dimensions:</b>	Height: 4.50" (114mm) Width: 2.75" (69mm) Depth: 1.75" (44mm) Projects: 0.44" (11mm) from mounting surface
<b>Mounting:</b>	Steel City #52171 box with Steel City #52C14 plaster ring, or Alpha Communications® Model # <b>IH358</b> box with <b>IH357</b> ring, or EXACT EQUAL. Vertical mount.
<b>Construction:</b>	Flame retardant type ABS plastic faceplate. Switches and electronic components are circuit board mounted.
<b>Connections:</b>	Plug-in connectors.

## REQUIRED COMPONENTS

- AlphaLinQ™ 100 Annunciator unit and system components
- **AC152** Control Unit (req. SS106 Transformer)
- **AC153** Third Priority Control Unit

## OPTIONAL COMPONENTS

- **CDL101LED** Corridor Dome Light w/1 White LED
- **CDL102LED** Corridor Zone Light w/1 White and 1 Red LED
- **VPS101** Single Visual Patient Station
- **VPS102** Double Visual Patient Station
- **VSS110** Visual Staff Station
- **EPS155** Emergency Pull/Push Station (Toilet)
- **EPS337** Emergency Pull/Push Station (Shower)
- **EPS339** Emergency Push Station (Mushroom Head)
- **VDS150** Duty Station
- **CA015K** Nylon pull cord sets
- **CA016K** Thermoplastic Polyurethane (TPU) plastic pull cord sets

---

### Alpha Communications

42 Central Drive • Farmingdale • NY • 11735-1202 • Phone: (631) 777-5500 • Fax: (631) 777-5599  
TOLL-FREE: (800) 666-4800 • Web: [www.alphacommunications.com](http://www.alphacommunications.com) • Email: [info@alphacommunications.com](mailto:info@alphacommunications.com)

Copyright© 1998-2023 Alpha Communications® - All Rights Reserved.

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.