

PRIMEX

Product Specification

Cat5e Jacks

90° & 180° UTP Keystones

1. SUMMARY

The Primex Cat5e 90° and 180° UTP keystone jacks fit in standard wall plates and provide easy high-speed data access.

Available in either 90 and 180 degree configurations, these UTP keystones are UL-Listed and offer dual 568A/B wiring labels for easy installation.

Pairing them with Primex wall plates in 1-4 port configurations offers versatile installation options.

2. DIMENSIONS

SIZE Cat5e 90°: H 1.33" / W 0.57" / D 0.63"

SIZE Cat5e 180°: H 1.21" / W 0.57" / D 0.63"

3. FEATURES & BENEFITS

- Available in 90° or 180° configurations.
- Dual 568A/B wiring label.
- 110 Universal IDC.
- Includes dust cover for protection of socket from dust.
- Pairs with Primex wall plates in 1-4 port configurations.
- UL/CUL listed
- Applicable specifications:
ANSI/TIA/EIA-568-C.2-1, ISO/IEC 11801 2nd edition: 2002, EN50173-1: 2002, FCC Part 68

4. CONFIGURATIONS


Part #	Description
125-0949-WT	Cat5e, 110 IDC, 90° HD (White)
125-0949-BL	Cat5e, 110 IDC, 90° HD (Blue)
125-0949-BK	Cat5e, 110 IDC, 90° HD (Black)
125-0949-RD	Cat5e, 110 IDC, 90° HD (Red)
125-0948-WT	Cat5e, 110 IDC, 180° HD (White)
125-0948-BL	Cat5e, 110 IDC, 180° HD (Blue)
125-0948-YL	Cat5e, 110 IDC, 180° HD (Yellow)
125-0948-RD	Cat5e, 110 IDC, 180° HD (Red)





Cat5e 180° Keystone




Pairs with standard keystones.



Cat5e 90° Keystone



Cat5e 180° Keystone



FOR MORE INFORMATION CONTACT:

☎ 1.604.881.7875 📠 1.604.881.7835

www.primex.com

