

# Product data sheet

Specifications



## Rack PDU, Basic, Zero U, 20A, 120V, (14)5-15

AP9551

### Overview

**Lead time** Usually in Stock

### Main

**Color** Black

**Product or Component Type** PDU

**PDU Type** Basic

**Cord length** 12 ft (3.7 m)

**Number of cables** 1

**Provided Equipment** Rack Mounting brackets  
Toolless Mounting Kit  
User Manual

### Complementary

**Input Voltage** 100 V  
120 V

**Height** 24.02 in (61 cm)

**Width** 1.65 in (4.2 cm)

**Output Voltage** 120 V

**Depth** 1.73 in (4.4 cm)

**Product Weight** 4.9 lb(US) (2.2 kg)

**Mounting Location** Side

**Mounting preference** No preference

**Input Plug Type** NEMA L5-20P

**Mounting Mode** Rack-mounted

**Rack units** 0U

**Mounting position** Vertical

**Line Rated Current** 16 A

**Acceptable Input Voltage** 90...132 V

**Max line current** 20 A

**Input current limits** 20 A

**Load Capacity** 1920 VA

**Input Frequency** 50/60 Hz

**Outlet type and quantity** 14 NEMA 5-15R

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Environment

<b>Product Certifications</b>	cUL Listed CSA UL Listed
<b>Ambient air temperature for operation</b>	32...113 °F (0...45 °C)
<b>Relative Humidity</b>	0...95 %
<b>Operating altitude</b>	0...10000 ft
<b>Ambient Air Temperature for Storage</b>	-13...149 °F (-25...65 °C)
<b>Storage Relative Humidity</b>	0...95 %
<b>Storage altitude</b>	0...50000 ft (0.0000000000...15240.0000000000 m)

## Ordering and shipping details

<b>GTIN</b>	731304021247
-------------	--------------

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	25.51 in (64.8 cm)
<b>Package 1 Width</b>	5.98 in (15.2 cm)
<b>Package 1 Length</b>	7.01 in (17.8 cm)
<b>Package 1 Weight</b>	6.44 lb(US) (2.92 kg)

## Contractual warranty

<b>Warranty</b>	2 years repair or replace
-----------------	---------------------------



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) **56**

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

[EU RoHS Directive](#) **Compliant**

REACH Regulation [REACH Declaration](#)

Halogen content performance **Product contains halogen above thresholds**

### Energy efficiency

Optimized Energy Efficiency **Energy efficient product**

## Use Again

### Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back **Yes**