



DEC0804A



Via Don Arrigoni, 5
24020 Rovetta (BG) – Italy
www.comelitgroup.com

SYSTEM INFORMATION	
CPU	RK3588
OS	Linux
Memory	LPDDR4 8GB; 16 GB EMMC
Network Interface	2x R45 10/100/1000Mbps
Audio Input/Output	- / 1 (RCA)
Alarm Input/Output	4 / 4
Other Interfaces	1x USB 3.0, 2x USB 2.0
Operational Mode	VMS mode (Comelit CCTV Manager) / Stand-alone mode (local web interface)
Supported Protocols	Comelit (Advance/Next IPNVR, AHDVDR and IP cameras), Onvif, RTSP
VIDEO PARAMETERS	
Video Output	-HDMI1 (up to 3840x2160, up to 7680x4320 by disabling HDMI2) -HDMI2 (up to 3840x2160) -HDMI3 (up to 3840x2160) -HDMI4 (up to 1920x1080) -VGA (up to 1920x1080, mirroring of HDMI1)
Single Screen Display Layout	1/4/9/16/25/36/64 CH
Supported Resolution	16MP, 12MP, 8MP, 5MP, 4MP, 3MP, 1080P, 720P, D1, CIF
Decoding Capability	4CH 16MP@30fps or 8CH 8MP@30fps or 12CH 5MP@30fps or 20CH 3MP@30fps or 32CH 1080P@30fps or 64CH 720P@30fps or 128CH D1@30fps or 255CH CIF@30fps
Supported Codec	H.264/H.265/MJPEG
HDMI Input	1 (up to 3840x2160)
GENERAL SPECS	
Power	DC 12V
Power Consumption	48W
Working Temperature	-10° / +50°
Working Humidity	10% ~ 90%
Dimensions	380 x 268 x 45mm (W x D x H)

