

# Product datasheet

Specifications



## Power Dist. Mod. 3x1 POLE 3 Wire RCD 32A 3xIEC309 480CM, 540CM, 600CM

PDM2332IEC-3P30R-2

### Overview

**Presentation** Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.

**Lead time** Usually Ships within 4 Weeks

### Main

**Main Input Voltage** 400 V 3 phases

**Main Output Voltage** 230 V

**Provided equipment** Installation guide

### Physical

**Colour** Grey

**Height** 25.4 cm

**Width** 43.2 cm

**Depth** 40.6 cm

**Net weight** 9.5 kg

### Input

**Network frequency** 50 Hz

**Max line current** 32 A

### Output

**Max current draw** 32 A

**Number of power socket outlets** 3 IEC 309 32 A

### Conformance

**product certifications** CE  
VDE

### Packing Units

**Unit Type of Package 1** PCE

**Number of Units in Package 1** 1

**Package 1 Height** 25.4 cm

**Package 1 Width** 40.6 cm

---

**Package 1 Length** 43.2 cm

---

**Package 1 Weight** 10.4 kg

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more about Green Premium >](#)




Take-back Transparency RoHS/REACH

## Resource performance


 Take-Back Program Available

---

## Well-being performance

 Mercury Free

---

 RoHS Exemption Information [Yes](#)

---

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

---

Eu Rohs Directive Compliant with Exemptions

---

Environmental Disclosure [Product Environmental Profile](#)

---

Circularity Profile [End of Life Information](#)

---

Image of product / Alternate images

Alternative

---

