

# HID Proximity Credentials



**ProxCard® II**

**ISOProx® II**

**DuoProx® II**

**Smart  
ISOProx II™**

**Smart  
DuoProx® II**

Base Part Number	1326	1386/1586	1336/1536	1397/1597	1398/1598
<b>Read Range: *</b>					
<b>ProxPoint® Plus</b>	Up to 3.0" (7.5 cm)		Up to 2.5" (6.5 cm)		
<b>MiniProx®</b>	Up to 5.5" (14.0 cm)		Up to 5.0" (12.5 cm)		
<b>Thinline® II</b>	Up to 5.5" (14.0 cm)		Up to 5.0" (12.5 cm)		
<b>ProxPro®</b>	Up to 8.0" (20.5 cm)		Up to 7.0" (18.0 cm)		
<b>ProxPro® II</b>	Up to 9.0" (23.0 cm)		Up to 8.0" (20.0 cm)		
<b>MaxiProx®</b>	Up to 29.0" (74.0 cm)		Up to 20.0" (51.0 cm)		
<b>EntryProx™</b>	Up to 3.0" (7.5 cm)		Up to 2.5" (6.5 cm)		
<b>Prox80™</b>	Up to 5.5" (14.0 cm)	Up to 5.0" (12.5 cm)		Up to 2.5" (6.0 cm)	
<b>Memory Size/ Application Area</b>	N/A				
<b>HID Proximity 125 kHz</b>	Yes				
<b>Contact Smart Chip Module Embeddable</b>	No			Yes**	
<b>Wiegand Strip</b>	No				
<b>Magnetic Stripe</b>	No	Yes	No	Yes	
<b>Printable ***</b>	Yes				
<b>Standard HID Artwork</b>	Optional				
<b>Slot Punch</b>	Vertical (standard)	Horizontal or Vertical Optional		Vertical Optional	
<b>Visual Security Options</b>	N/A	Yes			
<b>Additional Security Options</b>	Corp 1000				
<b>Warranty</b>	Lifetime				

\* Dependant upon installation conditions.

\*\* Contact smart chip module not included. Ask about HID's SMARTS Program for off-the-shelf contact smart chip embedded cards.

\*\*\* Some types of printing processes can take these credentials out of ISO compliance for thickness. Consult factory for more information.