# Product data sheet

Specifications



## APC Rack PDU 9000 Switched, ZeroU, 20A, 208V, (21) C13/C15 & (3) C19/C21, L620 Cord

APDU9959NA3

## Overview

| | |
|---|---|
| **Lead time** | Usually in Stock |

## Main

| | |
|---|---|
| **Color** | Black |
| **Product or Component Type** | PDU |
| **PDU Type** | Switched |
| **Provided Equipment** | Installation guide<br>Rack Mounting brackets<br>Safety guide |

## Complementary

| | |
|---|---|
| **Input Voltage** | 200 V<br>208 V |
| **Height** | 70.75 in (179.7 cm) |
| **Width** | 2.17 in (5.5 cm) |
| **Output Voltage** | 208 V<br>200 V |
| **Depth** | 1.81 in (4.6 cm) |
| **Product Weight** | 12.37 lb(US) (5.61 kg) |
| **Mounting Location** | Side |
| **Mounting preference** | No preference |
| **Input Plug Type** | IEC 60320 L6-20P |
| **Mounting Mode** | Not rack-mountable |
| **Rack units** | 0U |
| **USB compatible** | No |
| **Mounting position** | Vertical |
| **Communication Port Protocol** | SNMP<br>Redfish |
| **Line Rated Current** | 16 A |
| **Acceptable Input Voltage** | 100…240 V |
| **Input current limits** | 20 A |
| **Load Capacity** | 3300 VA |
| **Input Frequency** | 50/60 Hz |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Outlet type and quantity** | 21C13/C15<br>3C19/C21 |
| **Communication Network Type** | 10/100/1000BASE-T |

## Environment

| | |
|---|---|
| **Product Certifications** | cUL Listed<br>FCC part 15 class A<br>PSE |
| **Standards** | IEC 62368-1 |
| **Ambient air temperature for operation** | 23…140 °F (-5…60 °C) |
| **Relative Humidity** | 5…95 % |
| **Operating altitude** | 0...10000 ft |
| **Ambient Air Temperature for Storage** | -13…149 °F (-25…65 °C) |
| **Storage Relative Humidity** | 5…95 % |
| **Storage altitude** | 0…50000 ft (0.0000000000…15240.0000000000 m) |

## Ordering and shipping details

| | |
|---|---|
| **GTIN** | 731304356301 |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Number of Units in Package 1** | 1 |
| **Package 1 Height** | 78.82 in (200.2 cm) |
| **Package 1 Width** | 4.49 in (11.4 cm) |
| **Package 1 Length** | 6.50 in (16.5 cm) |
| **Package 1 Weight** | 17.33 lb(US) (7.86 kg) |

## Contractual warranty

| | |
|---|---|
| **Warranty** | 3 years repair or replace |

# Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

## Environmental footprint

| | |
|---|---|
| Carbon footprint (kg CO2 eq, Total Life cycle) | 2259 |
| Environmental Disclosure | Product Environmental Profile |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant with Exemptions |
| SCIP Number | 31346aed-552c-4a16-81d9-e683a383b6da |
| REACh Regulation | REACh Declaration |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Circularity Profile | End of Life Information |
| Removable battery | Yes |
| Take-back | No |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Image of product / Alternate images

**Alternative**



