# Desktop Computer AC Power Cable, NEMA 5-15P to C13 - 10A, 125V, 18 AWG, 25 ft. (7.62 m), Black

MODEL NUMBER: **P006-025**



Computer power cable allows you to connect your PC, printer or monitor into a surge protector, PDU or UPS with a NEMA 5-15R outlet.

### Features

**Desktop Computer Power Cord Connects PCs, Printers, Monitors and Other Equipment**This computer power supply cable is designed for home/office desktop computer applications. You can use it to connect a computer, monitor, printer, scanner or other device with a C14 power inlet to an AC wall outlet, surge protector, UPS system or PDU. The 25-ft. (7.62 m) length allows you great flexibility in placing equipment with respect to the power outlet.

### Highlights

- Recommended for powering computers, printers and other home/office peripherals
- 25-ft. (7.62 m) length allows great flexibility in placing devices in relationship to AC outlet
- NEMA 5-15P to C13 extension cord is ideal replacement for worn-out or missing cable

### Applications

- Connect devices like computers, printers and monitors to a PDU up to 25-ft. (7.62 m) away in your workstation
- Extend an existing power connection up to 25-ft. (7.62 m) to more easily place a device or reach a power source
- Provide a high-quality replacement for a worn-out or missing power cord

### Package Includes

- P006-025 NEMA 5-15P to C13 Computer Power Cable, 25-ft. (7.62 m), Black

## Specifications

| | |
|---|---|
| **OVERVIEW** | |
| UPC Code | 037332180568 |
| Device Compatibility | Computer; Monitor/HDTV; Printer; Server; UPS; PDU |
| Country/Region | North America |
| **INPUT** | |
| Maximum Input Amps | 10 |
| Voltage Compatibility (VAC) | 125 |
| **CONNECTIONS** | |
| Side A - Connector 1 | NEMA 5-15P |
| Side B - Connector 1 | IEC-320-C13 |
| **PHYSICAL** | |

| | |
|---|---|
| Color | Black |
| Cable Jacket Color | Black |
| Cable Jacket Material | PVC |
| Cable Jacket Rating | VW-1 |
| Power Cord Jacket Type | SJT |
| Cable Outer Diameter (OD) | 7.8mm |
| Number of Conductors | 3 |
| Wire Gauge (AWG) | 18 |
| Wire Gauge (OD - $mm^2$) | 0.82 |
| Cable Length (ft.) | 25 |
| Cable Length (m) | 7.62 |
| Shipping Dimensions (hwd / in.) | 14.17 x 11.81 x 0.50 |
| Shipping Dimensions (hwd / cm) | 35.99 x 30.00 x 1.27 |
| Shipping Weight (lbs.) | 1.59 |
| Shipping Weight (kg) | 0.72 |
| **ENVIRONMENTAL** | |
| Operating Temperature Range | -4° to 140°F (-20° to 60°C) |
| Storage Temperature Range | -4° to 140°F (-20° to 60°C) |
| Relative Humidity | 10% to 85% RH |
| **FEATURES & SPECIFICATIONS** | |
| Antibacterial | No |
| Angled Plug | No |
| High Voltage | No |
| Locking Plug | No |
| Coiled Power Cord | No |
| **STANDARDS & COMPLIANCE** | |
| Product Certifications | cUL Listed; UL Listed |
| Product Compliance | RoHS |
| **WARRANTY & SUPPORT** | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

1000 Eaton Boulevard
Cleveland, OH 44122
United States
https://tripplite.eaton.com

© 2025 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.