

## 2 CONDUCTOR 16 AWG STRANDED TYPE CMP/FPLP



### 1.0 SCOPE:

- 1.1 This cable consists of 2 conductors 16 AWG stranded bare copper; color-coded plenum rated PVC insulation; overall white plenum rated PVC jacket. Type CMP/FPLP  
UL Standards 444 & 1424  
NEC Articles 760 & 800

### 2.0 CONSTRUCTION:

#### 2.1 CONDUCTOR:

- 2.1.1 Material: Bare Copper
- 2.1.2 Size: 16 AWG
- 2.1.3 Construction: 19 Strand

#### 2.2 INSULATION:

- 2.2.1 Material: Plenum Rated PVC
- 2.2.2 Wall Thickness: .007" nom.
- 2.2.3 Color code:
  - 1-Black
  - 2-Red

### 2.3 JACKET:

- 2.3.1 Material: Plenum Rated PVC
- 2.3.2 Wall Thickness: .014" nom.
- 2.3.3 OD: .174" nom.
- 2.3.4 Color: White
- 2.3.5 Ripcord under jacket
- 2.3.6 Markings: PAIGE #2U16022B1 E191596  
16AWG 2/C (UL) CMP C(UL)US OR (UL)  
FPLP 75'C FT-6 ROHS II COMPLIANT  
REACH MADE IN USA  
(Ascending/Descending footage markings)

### 2.4 ELECTRICAL PROPERTIES

- 2.4.1 Temperature: -20°C to 75°C
- 2.4.2 Voltage: 300 Volt
- 2.4.3 Capacitance: 36 pF/ft. +/- 10%
- 2.4.4 Impedance: 53 ohms +/- 10%
- 2.4.5 DC Resistance: 4.15 ohms/M' @ 20°C

### 2.5 PUT-UPS:

- 2.5.1 1000' Box
- 2.5.2 Weight: 27 lbs / 1000'

The information and specifications described herein are subject to error or omission and to change without notice.

Paige provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Paige be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Paige has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.