



TBUS-4xl

Table Mount Modular Multi-Connection
Solution – Tilt-Up Lid



The TBUS-4xl is the enclosure of a new modular system with a tilt-up lid. A complete TBUS system requires the enclosure, an inner frame, a power socket, inserts and a power cord.

NOTE: The TBUS enclosure, power socket, power cord & inserts are purchased separately

FEATURES

Inner Frame - 2 different "T4F" inner frame options are available that can accommodate a combination of up to 4 power sockets, 6 cable pass-through or connector inserts, 1 long insert and up to 3 Kramer TOOLS

Power Sockets - 8 different "TS" single socket options are available to accommodate the power requirements worldwide

Power Cord - 8 different "C-AC" single power cords (and 3 "Y" power cords) for each power socket

Optional Accessories - TBUS Brackets, K-Able Box Cable Reels, Step-In Modules and Controllers are available

Cover - Manually opens & closes

Connector Depth - Adjustable

Installation Requirement - Table cutout of 225mm x 123mm (8.87" x 4.85")

Dimensions - Top plate: 24.3cm x 14.0cm (9.6" x 5.5") W, D; Enclosure: 20.3cm x 10.2cm x 13.0cm (8.0" x 4.0" x 5.1") W, D, H

Weight - TBUS-4xl: 1.35kg (2.8lbs) approx.; table clamps: 0.25kg (0.6lbs)



TECHNICAL SPECIFICATIONS

INCLUDED
ACCESSORIES:

OPTIONS: Passive wall plates and interfaces



CONFIGURATIONS

TBUS-4xl(B)	Enclosure - Black Sand Blasted Anodized Aluminum Top
TBUS-4xl(BC)	Enclosure - Silver Sand Blasted Anodized Aluminum Top