



TELGUARD

EXDL-0

LTE, 3G/4G AND
CDMA NETWORKS

L T E M U L T I B A N D
N O G R O U N D P L A N E
O M N I D I R E C T I O N A L A N T E N N A



PRODUCT FEATURES

- ▶ Mechanically robust for both Indoor/Outdoor applications
- ▶ Self-contained design requiring no ground plane
- ▶ Applicable for both 3G and 4G application
- ▶ Domestic LTE 700 band and Global LTE 2600 band
- ▶ WiMAX 2300/2500/2600 bands

MODEL NUMBER

EXDL-0

INCLUDES

- Antenna with integral radial ground plane connector
- Mounting Bracket
- TNC Adapter

Cables not included.

For TG-1 Express use CTXL-12.

For TG-1B, TG-4, and TG-7 series, use ACD-12/35/50/100.

TECHNICAL DATA

Frequency Range	698 - 960 MHz, 1710 - 2700 MHz
VSWR	
698-806 MHz	<2.5: 1.0
806-960 MHz	<2.0: 1.0
1710-2700 MHz	<2.0: 1.0
Peak Gain	
698-960 MHz	0 dBi
1710-1990 MHz	1.7dBi
2100-2700 MHz	2.9dBi
Polarization	Vertical
Pattern	Omnidirectional
Input Impedance	50Ω
Maximum Power	100 W
Mount	Included
Radome Material	High Heat ABS
Dimensions	3.45" H x 1.45" dia. (8.76 cm x 3.68 cm)