



CP Control Panel are available in sizes from one to six gangs with single or multiple switch configurations. Choose between momentary action switches that remains active as long as they're depressed or alternate action switches that alternate between open (disconnected) and closed (connected) each time they're pressed. Designed to work with door status or lock status sensors in order to supervise and control several entry points from one main location.

Features

Standard Features

- Switches mounted on wall plates with 430 stainless steel finish

Options

- Number of switches (1-24 total): Each gang accepts up to four switches, specify number of switches when ordering
- Switch type, specify: SPDT/DPDT, momentary/alternate
- Lens color: green, red, yellow, blue, white

- Illumination: None, 12 VDC, 24 VDC
- For a control panel that requires multiple switch colors, multiple switch types, or custom labelling, please contact factory for custom part numbers.

Specifications

Dimensions

- Switch: 5/8" x 7/8"
- Plate: varies based on finished good

Electrical

- N/O and N/C contacts rated 10A at 35 VDC or 120 VAC
- Switches terminated in 22AWG colored 12" leads
 - Common: white
 - N/C: red
 - N/O: blue
 - LED+: Yellow
 - LED-: Black

How To Order

MODEL	PLATE SIZE (GANGS)	SWITCH QUANTITY	SWITCH TYPE	LENS COLOR	ILLUMINATION
CP	2	8	A	R	V1
CP	1 - Gang	Up to 4 (max)	A - SPDT Momentary Action	G - Green	N - None
	2 - Gang	Up to 8 (max)	B - SPDT Alternate Action	R - Red	V1 - 12VDC
	3 - Gang	Up to 12 (max)	C - DPDT Momentary Action	Y - Yellow	V2 - 24VDC
	4 - Gang	Up to 16 (max)	D - DPDT Alternate Action	B - Blue	
	5 - Gang	Up to 20 (max)		W - White	
	6 - Gang	Up to 24 (max)			