

Standard Package

FiberFox MiniSeries Splicers 12R, 6S, 5C, 4S – The Most Complete Fusion Splicer Kit

MiniSeries Splicer	Cooling Tray	Car Charger
Precision Cleaver w/ Auto Bin & Soft Case	*One Tap* Cleaning Fluid	USB Firmware Update Cable
Extra Precision Cleaver (12R)	Lint Free Wipes (50)	Three-Hole Stripper
Thermal Stripper (All Kits)	Lint Free Swabs (100) (12R)	Phillips Screwdriver
- includes AC adapter, Brush	5x Magnifier w/ LED Light (12R)	Power Cord / AC Adapter
Two Battery Packs (All Kits)	V-Groove Cleaning Pen (12R)	Soft Cover User Manual / CD
Fiber Holders (2pr-250,900) (6S,5C,4S)	Anti Static Brush (12R)	Yellow Hard Case w/ Shoulder Strap
Fiber Holders (3pr-12f,250,900) (12R)	Sweeper Brush (12R)	SL60-100 Splice Sleeves (6S,5C,4S)
FOX-SOCHOLDER	SOC Heater Block	SL40R-50 Splice Sleeves (12R)
FOX-SOCHOLDER 2/3	Spare Electrodes (pair)	

Specifications

Splicing Method	Digitalized Active Alignment
Average Loss	SM(0.02dB) / MM(0.01dB) / DS(0.05dB) / NZDS(0.05dB) / G.657(0.02dB)
Return Loss	>>60dB
Splice Time	12s average SM / SM 7s Quick mode
Electrode Lifespan	>3,500 arcs
Applicable Fiber	SM(ITU-T G.652, MM(ITU-T G.651), DS(ITU-T G.653), NZDS(ITU-T G.655), IT-G657A, IT-G657B 0.25mm, 0.9mm, 2.0mm, 2.4mm, 3.0mm, FLAT(indoor cable)
Cleaved Length	Coating Diameter < 0.25mm = 5-16mm, Coating Diameter > 0.25mm = 8-16mm minimum
Coating Diameter	100-1000um
Cladding Diameter	80-150um
Heating Programs	Factory installed mode : 3, User installable mode : 23
Heating Time	Typical 18s
Protection Sleeve	40mm, 60mm, SOC-3.0, SOC-0.9
Data Output	Micro HDMI-USB master device
Splice Programs	8 user modes, User installable mode : 70+
Splice Memory	Up to 2000 records
Battery	Typical 200 Cycles (Splice & Heat) / single battery <2 Batteries Standard>
Power Supply	AC 100-240V input or DC 9-14V
Monitor	Color 4.3" LCD monitor, with Touch Screen (Tempered Glass)
Cameras	2 CCD camera system
Magnification	XY : 150 times, X/Y : 300 times
Fiber Display	X/Y or XY, single X.Y
Weight	1.31Kg (without battery)
Size	122mm X 124mm X 138 mm
Wind Protection	The max wind speed 15m/s
Operating Environment	Elevation 0-5000 meters, -15~60°C, 0-95% relative humidity
Storage Condition	Temperature -40 to 80°C, 0-95% relative humidity, battery -20-30°C
Pull Test	1.96-2.25N (standard)
Attenuation splicing	Range : 0.1dB ~ 20dB (0.1dB step)

www.FiberFoxAmerica.com



Mini 4S

4 Motors
Active Alignment Splicer



4 Motors
Active Alignment Splicer
Compatible with all leading Splice-on Connectors

1.31
kg

400
cycles

7
sec

0.02
dB

Characteristic




900 μ m fiber holder included
250 μ m fiber holder included



Cooling tray included



Compatible with all leading
Splice on Connectors
** FiberFox Legrand AFL Sumitomo
Belden Hubbell and more



Mini 4S

1.31kg
(Without Battery)

122 x 124 x 138 mm



Thermal Stripper
Included



Industry's First!
Two Batteries are Included in Standard Package
- 400 cycles (splicing & heating) with Two Batteries



Full Touch Screen
- GUI Interface
- Tempered Glass

01

Performance


Perfect performance
under any environmental conditions

Temperature
-15~60°C

relative humidity
0~95%


Elevation
0~5000meter

The max wind
speed 15m/s



02

SOC
Compatible



03

Durability



Anti-shock



Dustproof

Waterproof



04

FTTH
Solution