



Network

PTZ

QNP-6320

2MP PTZ Camera



Key Features

- Max. 2MP resolution
- 4.44~142.6mm (32x) lens
- Day & Night (ICR), WDR, DIS (Built-in gyro sensor)
- Intelligent Analytics
- H.264, H.265, MJPEG codec, WiseStreamII
- Micro SD/SDHC/SDXC 1slot 256GB

Compatible Devices



SHP-1520FW



SBP-301HMW3

QNP-6320

2MP PTZ Camera



Specifications

Video

Imaging Device	Size	1/2.8"
	Type	CMOS
Resolution	320x240, 1280x720, 1280x1024, 720x480, 1280x960, 800x448, 800x600, 720x576, 640x360, 640x480, 1024x768, 1920x1080	
Max. Framerate	H.265/H.264	60fps/50fps(60Hz/50Hz)
	MJPEG	30fps
Min. Illumination (Lux)	Color(1/30sec, 30IRE)	0.05
	BW(1/30sec, 30IRE)	0.005

Lens

Focal Length (mm)	4.44~142.6	
Zoom Ratio	Optical	32x
	Digital	32x
Max Aperture Ratio (F number)	Wide	1.6
	Tele	4.4
Angular Field of View	Horizontal	64.66°~2.29°
	Vertical	38.08°~1.30°
Min. Object Distance	1.5m(4.92ft)	
Focus Control	Oneshot AF, Focus save	
Lens Type	DC auto iris	

Pan / Tilt / Rotate

Pan / Tilt / Rotate Range	Pan	360° Endless
	Tilt	90°~-15°
Pan Speed	Preset	Max. 700°/sec
	Manual	0.024°/sec~200°/sec
Tilt Speed	Preset	Max. 300°/sec
	Manual	0.024°/sec~200°/sec
Sequence	Trace, Swing, Tour, Schedule, Group(6ea), Preset(300ea), Auto Run	
Preset Accuracy	±0.2°	

Operational

Direction Indicator		Support
Day & Night		Auto(ICR)
Backlight Compensation		HLC, BLC, WDR, SSSR
Wide Dynamic Range (dB)		120
Digital Noise Reduction		SSNR V
Digital Image Stabilization		Support(built-in gyro sensor)
Defog		Support
Motion Detection	Quantity	8ea
	Shape	8point Polygonal zones
Privacy Masking	Quantity	32ea
	Shape	4point Quadrangle zones
	Color / Option	Gray, White, Black, Blue, Green, Mosaic, Red
Gain Control		Off, Max gain, Manual
White Balance		Sodium, Indoor, Manual, AWC, ATW, Mercury, Outdoor
Electronic Shutter	Mode	Anti flicker, Minimum, Maximum
	Speed Range	2~1/12,000sec
Video Rotation		Flip&Mirror
Alarm Interface	In/Out	Input 4ea / Output 2ea
Alarm Triggers		Alarm input, Network disconnect, Analytics
Alarm Events When Alarm Trigger Occurred		Handover: PTZ preset, send message by HTTP/HTTPS/TCP, Notification: e-mail, File upload(image): e-mail/FTP, Recording: SD/SDHC/SDXC or NAS recording at event triggers, Alarm output
Audio In		Selectable(mic in/line in)
Audio Out		Line out
Auto Tracking		Support

Analytics

Analytics Events	Normal	Shock detection, Motion detection, Virtual area(Lotering, Intrusion, Enter/Exit, Appear/Disappear), Virtual line(Crossing, Direction) , Tampering, Audio detection
------------------	--------	--

Network

Ethernet	RJ-45(10/100BASE-T)
Video Compression	H.265/H.264: Main/High, MJPEG
Audio Compression	G.726: 16Kbps, 24Kbps, 32Kbps, 40Kbps, G.726(ADPCM) 8KHz, G.711 8KHz, AAC-LC: 48Kbps at 16KHz, G.711 u-law /G.726 selectable
Smart Codec	WiseStream II , Manual
Bitrate Control	H.265/H.264: CBR or VBR, MJPEG: VBR

Network

Streaming	Unicast	Up to 20 users
	Multicast	Support
	Multiple Streaming	Up to 10 profiles
Protocol		NTP, RTP(UDP), NTCIP 1205, IPv4, HTTPS, FTP, TCP/IP, ARP, DHCP, RTCP, IPv6, UDP/IP, Bonjour, DNS, SNMPv1/v2c/v3(MIB-2), RTP(TCP), SSL/TLS, QoS, SMTP, DDNS, IGMP, HTTP, UPnP, LLDP, RTSP, ICMP, SRTP(TCP, UDP Unicast)
Application Programming Interface	ONVIF	T, S, G
	Others	SUNAPI(HTTP API), Hanwha Vision Open Platform
Direct Cloud Connection		Optional (needs gateway)

Security

OS / Firmware Protect	Encrypted firmware
User authentication	Prevent brute-force attack, Digest authentication
Network authentication	IEEE 802.1X(EAP-TLS, EAP-LEAP, EAP-PEAP, MSCHAPv2)
Secure Communication	WSS(WebSocket Secure), HTTPS, SRTP
Access Control	IP-based access control
Data Protect	Encrypt compress for live recording file export, Encryption credentials
Audit	Access / System / Event Log management
Device ID	Device certificate(Hanwha Vision Root CA)

General

Memory	RAM	1GB
	Flash	256MB
Edge Storage	Micro SD/SDHC/SDXC	Max. 256GB x 1slot

Environmental & Electrical

Operating Condition	Temperature	-10°C~+55°C(+14°F~+131°F)
	Humidity	0~95% RH(non-condensing)
Storage Condition	Temperature	-30°C~+60°C(-22°F~+140°F)
	Humidity	0~95% RH(non-condensing)
Input Voltage	PoE+(IEEE802.3at, Class4)	
Power Consumption	PoE	Max. 14.5W, Typical 12W
	110VAC	Non

Mechanical

Color	White
Material	Plastic
RAL Code	RAL9003
Product Dimensions	ø152x218mm(ø5.98x8.58")

Mechanical

Product Weight	1700g(3.75 lb)
----------------	----------------

Certifications & Standards

EMC	RCM AS-NZS CISPR 32 Class A, VCCI CISPR 32 Class A, IC Regulation ICES-003 Issue 7 Class A, FCC 47 CFR 15 Subpart B Class A, CE/UKCA - EN55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3
Safety	UL 62368-1, CAN/CSA C22.2 NO. 62368-1
Environment	IEC/EN 63000

DORI (EN62676-4 standard)

Detect (25PPM/ 8PPF)	Wide	60.7m(199.1ft)
	Tele	1921.3m(6303.4ft)
Observe (63PPM/ 19PPF)	Wide	24.3m(79.6ft)
	Tele	768.5m(2521.4ft)
Recognize (125PPM/ 38PPF)	Wide	12.1m(39.8ft)
	Tele	384.3m(1260.7ft)
Identify (250PPM/ 76PPF)	Wide	6.1m(19.9ft)
	Tele	192.1m(630.3ft)

QNP-6320

2MP PTZ Camera



CAD

Unit: mm [inch]

