# Product data sheet

Specifications



## Rack Mount, Security and Environmental Appliance, NetBotz, 750

NBRK0750

## Overview

| | |
|---|---|
| **Presentation** | The NetBotz Rack Monitor 750 provides integrated surveillance,sensing, access control, and advanced alerting for IT environmentsof all sizes, from single-rack edge networks to large data centers. |
| **Lead time** | Usually in Stock |

## Main

| | |
|---|---|
| **Product or Component Type** | Industrial rack PC |
| **Range of Product** | Netbotz |
| **Number of rack unit** | 1U |
| **Communication Port Protocol** | A-Link<br>DHCP<br>HTTPS<br>IPv4<br>SNMP v1<br>SNMP v3<br>SSH v2<br>TCP/IP |
| **Provided Equipment** | Rack Mounting brackets<br>Temperature/Humidity Sensor<br>USB cable |
| **Product Compatibility** | Rack Sensor Pod 150<br>Room Sensor Pod 155 |

## General

| | |
|---|---|
| **Camera Frame Rate** | Up to 30fps |
| **Display Resolution** | Up to 1280x1024 |
| **APC Universal Sensors Supported** | 0-5V<br>Door contact<br>Dry Contact<br>Humidity<br>Smoke<br>Fluid Spot Leak<br>Temperature<br>Vibration |
| **Number of Universal Sensor Ports** | 6 |
| **Number of Sensor Pods Supported** | 12 |
| **Number of Universal Sensors Supported** | 78 |
| **Number of Cameras Supported** | 4 |

## Physical

| | |
|---|---|
| **Color** | Black |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Height** | 1.69 in (4.3 cm) |
| **Width** | 17.01 in (43.2 cm) |
| **Depth** | 7.01 in (17.8 cm) |
| **Product Weight** | 5.40 lb(US) (2.45 kg) |
| **Mounting Location** | Front<br>Rear |
| **Mounting preference** | No preference |
| **Mounting Mode** | Rack-mounted |
| **Mounting position** | Horizontal |

## Conformance

| | |
|---|---|
| **Standards** | CSA C22.2 No. 60950-1-03<br>FCC Part 15 class A<br>ICES-003<br>UL 60950-1 |
| **Product Certifications** | 2014/30/EU<br>AS/NZS 3548 (C-Tick) Class A<br>CE<br>EMC Directive 2004/108/EC<br>VCCI Class A |

## Environmental

| | |
|---|---|
| **Ambient air temperature for operation** | 32…104 °F (0…40 °C) |
| **Operating altitude** | 0...10000 ft |
| **Relative Humidity** | 0…95 % |
| **Ambient Air Temperature for Storage** | 5…149 °F (-15…65 °C) |
| **Storage altitude** | 0…50000 ft (0.0000000000…15240.0000000000 m) |
| **Storage Relative Humidity** | 0…95 % |

## Communications & Management

| | |
|---|---|
| **Communication Network Type** | RJ-45 10/100/1000 Base-T |

## Ordering and shipping details

| | |
|---|---|
| **GTIN** | 731304344407 |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Number of Units in Package 1** | 1 |
| **Package 1 Height** | 4.53 in (11.500 cm) |
| **Package 1 Width** | 12.40 in (31.500 cm) |
| **Package 1 Length** | 21.06 in (53.500 cm) |
| **Package 1 Weight** | 9.178 lb(US) (4.163 kg) |
| **Unit Type of Package 2** | S04 |
| **Number of Units in Package 2** | 2 |
| **Package 2 Height** | 11.81 in (30 cm) |
| **Package 2 Width** | 15.75 in (40 cm) |

| | |
|---|---|
| **Package 2 Length** | 23.62 in (60 cm) |
| **Package 2 Weight** | 19.789 lb(US) (8.976 kg) |
| **Unit Type of Package 3** | P12 |
| **Number of Units in Package 3** | 8 |
| **Package 3 Height** | 17.72 in (45.000 cm) |
| **Package 3 Width** | 31.50 in (80.000 cm) |
| **Package 3 Length** | 47.24 in (120.000 cm) |
| **Package 3 Weight** | 105.610 lb(US) (47.904 kg) |

## Contractual warranty

| | |
|---|---|
| **Warranty** | 2 years |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Carbon footprint (kg CO2 eq, Total Life cycle) | 691 |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | No |
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant with Exemptions |
| REACh Regulation | REACh Declaration |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Take-back | No |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Image of product / Alternate images

**Alternative**





