

Product data sheet

Specifications



Cable, UPS Signaling for IBM AS/400 and IBMi (IBM Power Systems)

AP98275

Overview

Lead time Usually in Stock

Physical

Height 1.50 in (3.8 cm)

Width 7.01 in (17.8 cm)

Depth 5.98 in (15.2 cm)

Product Weight 0.79 lb(US) (0.36 kg)

Mounting Mode Not rack-mountable

Connector B SUB-D 9 male Simple Signaling

Connector A SUB-D 9 male Simple Signaling

Output

Number of port 1

Environmental

Storage Relative Humidity 0...95 %

Storage altitude 0...50000 ft (0.0000000000...15240.0000000000 m)

Ambient air temperature for operation 32...113 °F (0...45 °C)

Relative Humidity 0...95 %

Operating altitude 0...50000 ft

Ambient Air Temperature for Storage 5...113 °F (-15...45 °C)

Ordering and shipping details

GTIN 731304293422

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 2.01 in (5.1 cm)

Package 1 Width 6.50 in (16.5 cm)

Package 1 Length 9.25 in (23.5 cm)

Package 1 Weight 0.99 lb(US) (0.45 kg)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Contractual warranty

Warranty

2 years repair or replace



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant

SCIP Number

1cdb2fed-a06f-4574-913d-8df8e70936b2

REACH Regulation

[REACH Declaration](#)

California proposition 65

WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Halogen content performance

Product contains halogen above thresholds

Energy efficiency

Optimized Energy Efficiency

Energy efficient product

Use Again

Repack and remanufacture

Circularity Profile

[End of Life Information](#)

Take-back

Yes

WEEE

 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.