

# Product data sheet

Specifications



## Rack PDU, Basic, Zero U, 12.5kW, 208V, (30)C13, (6)C19; 10ft input Cord

AP7598

### Overview

**Lead time** Usually in Stock

### Main

**Color** Black

**Product or Component Type** PDU

**PDU Type** Basic

**Cord length** 10 ft (3.05 m)

**Number of cables** 1

**Provided Equipment**  
Cord retention bracket(s)  
Documentation CD  
Installation guide  
Rack Mounting brackets  
Toolless Mounting Kit

### Complementary

**Input Voltage** 208 V 3 phase

**Height** 70.00 in (177.8 cm)

**Width** 2.20 in (5.6 cm)

**Output Voltage** 208 V

**Depth** 3.50 in (8.9 cm)

**Product Weight** 19.38 lb(US) (8.79 kg)

**Mounting Location** Side

**Mounting preference** No preference

**Mounting Mode** Rack-mounted

**Rack units** 0U

**Mounting position** Vertical

**Max line current** 35 A

**Input current limits** 35 A

**Load Capacity** 12500 VA

**Input Frequency** 50/60 Hz

**Number of input connectors** 1 CS8365

**Outlet type and quantity**  
30 IEC 60320 C13  
6 IEC 60320 C19

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Environment

<b>Product Certifications</b>	cUL Listed UL Listed
<b>Standards</b>	CSA C22.2 No. 60950-1-03 UL 60950-1
<b>Ambient air temperature for operation</b>	23...113 °F (-5...45 °C)
<b>Relative Humidity</b>	5...95 %
<b>Operating altitude</b>	0...10000 ft
<b>Ambient Air Temperature for Storage</b>	-13...149 °F (-25...65 °C)
<b>Storage Relative Humidity</b>	5...95 %
<b>Storage altitude</b>	0...50000 ft (0.0000000000...15240.0000000000 m)

## Ordering and shipping details

<b>GTIN</b>	731304226864
-------------	--------------

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	82.99 in (210.8 cm)
<b>Package 1 Width</b>	5.00 in (12.7 cm)
<b>Package 1 Length</b>	5.98 in (15.2 cm)
<b>Package 1 Weight</b>	26.21 lb(US) (11.89 kg)

## Contractual warranty

<b>Warranty</b>	2 years repair or replace
-----------------	---------------------------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 223

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant

REACH Regulation [REACH Declaration](#)

Halogen content performance Product contains halogen above thresholds

### Energy efficiency

Optimized Energy Efficiency Energy efficient product

## Use Again

### Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back Yes

Image of product / Alternate images

Alternative

---



