

# Product data sheet

Specifications



APC Back-UPS Pro, 1350VA/  
810W, Tower, 120V, 10x NEMA  
5-15R outlets, Sine Wave, AVR,  
USB Type A + C ports, LCD, User  
Replaceable Battery

BR1350MS

Product availability: Stock - Normally stocked in distribution facility

## Overview

Lead time Usually in Stock

## Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Kw Rating	810 W
Rated power in VA	1350 VA
Product or Component Type	Uninterruptible power supply (UPS)
Input Connection Type	NEMA 5-15P
output connection type	6 NEMA 5-15R 4 NEMA 5-15R surge
Cable length	6 ft (1.8 m)
Number of cables	1
Battery Type	Lead-Acid battery
Range of Product	Back-UPS Pro

## Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>
Included Battery Modules	1
Battery Slots Empty	0
Typical recharge time	16 h
RBC Quantity	2
Battery Charge Power (Watts)	10 W rated
Battery life	3...5 year(s)
Replacement battery	<a href="#">APCRBC161</a>
Extendable Run Time	0

## General

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Provided equipment</b>	Coaxial cable User Manual USB cable
<b>product web sub-family</b>	Gaming performance
<b>Number of power module free slots</b>	0
<b>Number of power module filled slots</b>	0
<b>Redundant</b>	No

## Physical

<b>Height</b>	10.24 in (26 cm)
<b>Width</b>	3.94 in (10 cm)
<b>Depth</b>	14.49 in (36.8 cm)
<b>Product Weight</b>	25.8 lb(US) (11.7 kg)
<b>Mounting preference</b>	No preference
<b>Mounting Mode</b>	Not rack-mountable
<b>Two post mountable</b>	0
<b>USB compatible</b>	No

## Input

<b>Input Frequency</b>	60 Hz +/- 3 Hz
<b>Plug standard</b>	NEMA 5-15P
<b>Efficiency at full load</b>	88...147 V
<b>Maximum Input Current per Phase</b>	12 A
<b>Switching current capacity</b>	15 A

## Output

<b>Max Configurable Power (Watts)</b>	810 W
<b>Output frequency</b>	60 Hz +/- 3 Hz sync to mains
<b>Topology</b>	Line Interactive
<b>Waveform Type</b>	Sine wave
<b>Maximum configurable power in VA</b>	1350 VA
<b>Transfer Time</b>	8ms typical : 10 ms maximum

## Conformance

<b>Product Certifications</b>	ENERGY STAR V2.0 (USA) NOM TUV C-US certified
<b>Equipment protection policy</b>	Lifetime : \$500000

## Environmental

<b>Ambient air temperature for operation</b>	32...104 °F (0...40 °C)
<b>Relative Humidity</b>	0...95 % non-condensing
<b>Operating altitude</b>	0...10000 ft

Ambient Air Temperature for Storage	5...104 °F (-15...40 °C)
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...10000 ft (0.0000000000...3048.0000000000 m)
Acoustic level	45 dBA

## Communications & Management

control panel	Multi-function LCD status and control console
---------------	---

## Surge Protection and Filtering

Surge energy rating	1080 J
Filtering	Full time multi-pole noise filtering :5% of IEEE surge let-through : zero clamping response time: in

## Ordering and shipping details

Category	11309-APC RESALE PRODUCTS
Discount Schedule	APC1
GTIN	00731304335399
Returnability	No
Country of origin	PH

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.12 in (35.87 cm)
Package 1 Width	18.98 in (48.2 cm)
Package 1 Length	8.78 in (22.3 cm)
Package 1 Weight	29.3 lb(US) (13.3 kg)
SCC14	10731304335396

## Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant with Exemptions

SCIP Number

019b51cf-d7f1-4f06-ac85-1378fc94c7aa

REACH Regulation

[REACH Declaration](#)

California proposition 65

**WARNING:** This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### Energy efficiency

Optimized Energy Efficiency

Energy efficient product

 [ENERGY STAR®](#)

ENERGY STAR UPS V2.0 (USA)

## Use Again

### Repack and remanufacture

Circularity Profile

[End of Life Information](#)

Removable battery

User replaceable

Take-back

Yes

Image of product / Alternate images

Alternative

---

