Product data sheet

Specifications



APC Symmetra LX Battery Module

SYBT5

Overview

Presentation	Extended run power protection for servers, networks, and telecommunications
Lead time	Usually in Stock

Main

Product or Component Type	Battery accessory
Number of rack unit	0U
Number of cables	1.0
Battery Type	Lead-Acid battery
Provided Equipment	Installation guide
Range of Product	Symmetra Battery Systems

Batteries & Runtime

Battery location	Internal Battery
Battery blocks per string	10
Battery Slots Empty	0
Included Battery Modules	0
Device mounting	Enclosed battery cartridge
Battery Voltage	120 V
RBC Quantity	1

Physical

Height	5.51 in (14 cm)
Width	8.27 in (21 cm)
Depth	21.50 in (54.6 cm)
Product Weight	64.2 lb(US) (29.1 kg)
Mounting Mode	Not rack-mountable
USB compatible	No

Conformance

Standards	UL 1778
Product Certifications	CSA

Environmental

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient air temperature for operation	32…104 °F (0…40 °C)
Operating altitude	0...10000 ft
Relative Humidity	0…95 %
Ambient Air Temperature for Storage	5…113 °F (-15…45 °C)
Storage altitude	0…15000 ft (0.0000000000…4572.0000000000 m)
Storage Relative Humidity	0…95 %

Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	731304218869
Returnability	No
Country of origin	PH

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.63 in (27.000 cm)
Package 1 Width	11.42 in (29.000 cm)
Package 1 Length	29.92 in (76.000 cm)
Package 1 Weight	67.241 lb(US) (30.500 kg)
Unit Type of Package 2	P12
Number of Units in Package 2	8
Package 2 Height	29.53 in (75.000 cm)
Package 2 Width	31.50 in (80.000 cm)
Package 2 Length	47.24 in (120.000 cm)
Package 2 Weight	564.384 lb(US) (256.000 kg)

Contractual warranty

Warranty	2 years repair or replace

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	1

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

Repack and remanufacture

Take-back	Yes

Image of product / Alternate images

Alternative







