Specifications

Eaton T8S-A-CB



Catalog Number: T8S-A-CB

Eaton Basic rack PDU, 1U, C20 input, 3.33 kW max, 110-125V, 12A, 0 ft cord (hardwired), Single-phase, Outlets: (8) 5-15R

General specifications

Product Name
Eaton basic PDU

Catalog Number
T8S-A-CB

UPC
786685287614

Product Length/Depth
0.0001 in

Product Height
0.0001 in

Product Width
0.0001 in

Product Weight
0.0001 lb

Compliances
Contact Manufacturer

Certifications
UL Listed

Powering Business Worldwide

Product specifications

Form factor
1U

Outlet control
No

Phase
Single-phase

Wattage
3.33 kW max

Amperage Rating
12A

Input voltage
110-125V

Input connection
C20

Outlets
(8) 5-15R

Cord length
Hardwired

Frequency rating
50-60 Hz

Operating Temperature
0° to 60°C (32° to 140°F)

Resources

Certification reports
Eaton RoHS Declaration of Conformity: ePDU G3

Eaton RoHS declaration of conformity: ePDU G3

Drawings
Eaton PDU T8S-A-CB technical drawing

Installation instructions
Eaton ePDU G3 troubleshooting guide

Manuals and user guides
Eaton ePDU G3 installation and connectivity quick start

Eaton ePDU G3 operations manual

Eaton ePDU G3 1U and 2U installation addendum

Eaton ePDU G3 replace and configure eNMC module

Specifications and datasheets
Eaton Specification Sheet - T8S-A-CB

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia