

Product data sheet

Specifications



Rack PDU, Basic, 1U, 30A, 208V, (4) C19s



AP9570

Overview

Lead time Usually in Stock

Main

Color Black

Product or Component Type PDU

PDU Type Basic

Cord length 10 ft (3.05 m)

Number of cables 1

Provided Equipment Installation guide
Rack Mounting brackets

Complementary

Input Voltage 200 V
208 V
230 V

Height 1.73 in (4.4 cm)

Width 17.60 in (44.7 cm)

Output Voltage 208 V

Depth 2.52 in (6.4 cm)

Product Weight 6.02 lb(US) (2.73 kg)

Mounting Location Front
Rear

Mounting preference No preference

Input Plug Type NEMA L6-30P

Mounting Mode Rack-mounted

Rack units 1U

Mounting position Horizontal

Line Rated Current 24 A

Acceptable Input Voltage 200...240 V

Max line current 30 A

Input current limits 30 A

Load Capacity 4992 VA

Input Frequency 50/60 Hz

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Outlet type and quantity	4 IEC 60320 C19
--------------------------	-----------------

Environment

Product Certifications	cUL Listed METI Denan PSE UL Listed
------------------------	--

Standards	UL 60950
-----------	----------

Ambient air temperature for operation	32...113 °F (0...45 °C)
---------------------------------------	-------------------------

Relative Humidity	0...95 %
-------------------	----------

Operating altitude	0...10000 ft
--------------------	--------------

Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
-------------------------------------	----------------------------

Storage Relative Humidity	0...95 %
---------------------------	----------

Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)
------------------	--

Ordering and shipping details

GTIN	731304213086
------	--------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	2.76 in (7 cm)
------------------	----------------

Package 1 Width	9.02 in (22.9 cm)
-----------------	-------------------

Package 1 Length	18.27 in (46.4 cm)
------------------	--------------------

Package 1 Weight	8.51 lb(US) (3.86 kg)
------------------	-----------------------

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 70

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant

REACH Regulation [REACH Declaration](#)

Halogen content performance Product contains halogen above thresholds

Energy efficiency

Optimized Energy Efficiency Energy efficient product

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back Yes

Image of product / Alternate images

Alternative

