

Product data sheet

Specifications



APC Smart-UPS RT Tower Isolation/Step-Down Transformer

SURT003

Overview

Lead time Special Order - Call for Quoted Lead Times

Main

Main Input Voltage	208 V 240 V
Product or Component Type	Transformer
Main Output Voltage	120 V 208 V
Other Output Voltage	240 V
Input Connection Type	NEMA L6-30P
Number of rack unit	3U
Cable length	3 ft (0.9 m)
Number of cables	1
Provided Equipment	Installation guide User Manual

Physical

Color	Black
Height	17.01 in (43.2 cm)
Width	5.12 in (13 cm)
Depth	25.98 in (66 cm)
Product Weight	125.27 lb(US) (56.82 kg)
Mounting Location	Front
Mounting preference	Lower
Mounting Mode	Rack-mounted with kit
USB compatible	No
Mounting position	Vertical

Input

Acceptable Input Voltage	180...264 V
Input current limits	30 A
Load Capacity	4800 VA
Input Frequency	50/60 Hz

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Output

Maximum Total Current Draw per Phase	30 A
--------------------------------------	------

Protection Type	Circuit breaker
-----------------	-----------------

Number of power socket outlets	8 NEMA 5-20R 2 NEMA L6-20R 1 NEMA L6-30R 1 NEMA L14-30R
--------------------------------	--

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
---------------------------------------	-------------------------

Relative Humidity	0...95 %
-------------------	----------

Operating altitude	0...10000 ft
--------------------	--------------

Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
-------------------------------------	----------------------------

Storage Relative Humidity	0...95 %
---------------------------	----------

Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)
------------------	--

Ordering and shipping details

GTIN	731304217800
------	--------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	13.66 in (34.7 cm)
------------------	--------------------

Package 1 Width	38.58 in (98 cm)
-----------------	------------------

Package 1 Length	23.74 in (60.3 cm)
------------------	--------------------

Package 1 Weight	140.30 lb(US) (63.64 kg)
------------------	--------------------------

SCC14	10731304217807
-------	----------------

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant with Exemptions

REACH Regulation

[REACH Declaration](#)

Use Again

Repack and remanufacture

[Circularity Profile](#)

[End of Life Information](#)

Take-back

Yes

WEEE

 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative





