Product data sheet

Specifications



APC Smart-UPS, Line Interactive, 1500VA, Rackmount 2U, 120V, 6x NEMA 5-15R outlets, SmartConnect Port+SmartSlot, AVR, LCD [TAA]

SMT1500RM2UCUS

Overview

Lead time	Usually in Stock

Main

Product or Component Type	Uninterruptible power supply (UPS)

Complementary

Communication port type	SmartConnect Ethernet port SmartSlot

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Battery Type	Lead-Acid battery
Extendable Run Time	0
Battery Charge Power (Watts)	144 W rated
Replacement battery	APCRBC159

General

Provided equipment	CD with software
Redundant	No

Physical

Number of rack unit	2U
color	Black
Height	3.39 in (8.6 cm)
Width	17.01 in (43.2 cm)
Depth	18.78 in (47.7 cm)
Product Weight	58.4 lb(US) (26.5 kg)
Mounting Mode	Rack-mounted

Input

Main Input Voltage	120 V

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Other Input Voltage	110 V 125 V
Input Connection Type	NEMA 5-15P
Efficiency at full load	75...154 V adjustable
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Main Output Voltage	120 V
Other Output Voltage	110 V 125 V
Kw Rating	1000 W
Rated power in VA	1440 VA
output connection type	6 NEMA 5-15R
Maximum configurable power in VA	1440 VA
Max Configurable Power (Watts)	1000 W
Topology	Line Interactive
Waveform Type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Conformance

Product Certifications	cULus ENERGY STAR V2.0 (USA) TAA compliance

Environmental

Relative Humidity	0…95 %
Storage Relative Humidity	0…95 %

Ordering and shipping details

GTIN	731304424420
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.25 in (23.5 cm)
Package 1 Width	24.02 in (61 cm)
Package 1 Length	23.23 in (59 cm)
Package 1 Weight	70.81 lb(US) (32.12 kg)

Compliance

Compliance	TAA

Contractual warranty

Warranty	3 Years

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration

Energy efficiency

ENERGY STAR®	ENERGY STAR UPS V2.0 (USA)

Use Again

Repack and remanufacture

Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

