

Product data sheet

Specifications



Rack PDU, Basic, Zero U, 14.4kW,
208V, (24)C13, (4)C19, (2)L6-30R;
3ft input Cord

AP7569

Overview

Presentation	Basic Rack PDU 14.4 kW solution for high density installations
Lead time	Usually in Stock

Main

Color	Black
Product or Component Type	PDU
PDU Type	Basic
Cord length	3 ft (0.9 m)
Number of cables	1
Provided Equipment	Cord retention bracket(s) Documentation CD Installation guide Rack Mounting brackets Toolless Mounting Kit

Complementary

Input Voltage	208 V 3 phase
Height	70.00 in (177.8 cm)
Width	2.20 in (5.6 cm)
Output Voltage	208 V 3 phase
Depth	3.74 in (9.5 cm)
Product Weight	16.14 lb(US) (7.32 kg)
Mounting Location	Side
Mounting preference	No preference
Mounting Mode	Rack-mounted
Rack units	0U
Mounting position	Vertical
Line Rated Current	40 A
Input current limits	50 A
Load Capacity	14400 VA
Input Frequency	50/60 Hz
Number of input connectors	1 CS8365

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Outlet type and quantity	2 NEMA L6-30R 24 IEC 60320 C13 4 IEC 60320 C19
---------------------------------	--

Environment

Product Certifications	cUL Listed CSA METI Denan UL Listed
Standards	UL 60950
Ambient air temperature for operation	23...113 °F (-5...45 °C)
Relative Humidity	5...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)

Ordering and shipping details

GTIN	731304240754
-------------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	80.98 in (205.7 cm)
Package 1 Width	12.24 in (31.1 cm)
Package 1 Length	3.11 in (7.9 cm)
Package 1 Weight	24.87 lb(US) (11.28 kg)

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) **191**

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

[EU RoHS Directive](#) **Compliant**

REACH Regulation [REACH Declaration](#)

Halogen content performance **Product contains halogen above thresholds**

Energy efficiency

Optimized Energy Efficiency **Energy efficient product**

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back **Yes**

Image of product / Alternate images

Alternative



