

# Product data sheet

Specifications



APC Netshelter Rack Automatic Transfer Switch, 1U, 20A, 200/208V, 2 L6-20 IN, 8 C13, 1 C19 OUT, 50/60Hz

AP4430A

## Overview

Lead time Usually in Stock

## Main

Main Input Voltage 200 V AC 1 phase  
208 V

Product or Component Type Automatic transfer switch

Main Output Voltage 200 V AC 1 phase  
208 V

Input Connection Type NEMA L6-20P 16 A 2P+E

Number of rack unit 1U

Cable length 8 ft (2.4 m)

Number of cables 2

Provided Equipment Mounting Hardware  
Rack Mounting brackets

## Physical

Color Black

Height 1.73 in (4.4 cm)

Width 17.01 in (43.2 cm)

Depth 9.29 in (23.6 cm)

Product Weight 10.65 lb(US) (4.83 kg)

Mounting Location Front  
Rear

Mounting preference No preference

Mounting Mode Rack-mounted

Mounting position Horizontal

## Input

Input Frequency 50/60 Hz

Line Rated Current 20 A

Acceptable Input Voltage 180...220 V

Max line current 20 A

Input current limits 20 A

Load Capacity 3300 VA

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Output

Maximum Total Current Draw per Phase	20 A
Number of power socket outlets	8 IEC 60320 C13 12 A 2P+E 1 IEC 60320 C19 16 A 2P+E
Number of power socket outlets	9
Protection Type	Without circuit breaker
Cord Length	8.005 ft (2.44 m)

## Conformance

Standards	EN 55022 Class A FCC Part 15 class A
-----------	-----------------------------------------

## Environmental

Ambient air temperature for operation	23...113 °F (-5...45 °C)
Relative Humidity	5...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0.0000000000...50000.0000000000 ft (0...15240 m)

## Ordering and shipping details

GTIN	731304432463
------	--------------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.29 in (23.6 cm)
Package 1 Width	23.62 in (60 cm)
Package 1 Length	14.02 in (35.6 cm)
Package 1 Weight	14.6 lb(US) (6.6 kg)

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 553

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number 31346aed-552c-4a16-81d9-e683a383b6da

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)**

Halogen content performance Product contains halogen above thresholds

## Use Again

### Repack and remanufacture

Circularity Profile [End of Life Information](#)

Removable battery Yes

Take-back Yes

WEEE  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

---

