# Product data sheet

Specifications



## APC Smart-UPS SRT 192V 5kVA and 6kVA RM Battery Pack [TAA]

SRT192RMBPUS

## Overview

| | |
|---|---|
| **Lead time** | Usually in Stock |

## Main

| | |
|---|---|
| **Product or Component Type** | Battery |
| **Number of rack unit** | 3U |
| **Battery Type** | Lead-Acid battery |
| **Provided Equipment** | Installation guide<br>Warranty card |
| **Range of Product** | Smart-UPS Battery Systems |

## Batteries & Runtime

| | |
|---|---|
| **Battery Slots Empty** | 0 |
| **Included Battery Modules** | 0 |
| **Device mounting** | Stand alone battery stack |
| **Battery Voltage** | 192V |
| **RBC Quantity** | 2 |
| **Replacement battery** | APCRBC140 |

## Physical

| | |
|---|---|
| **Color** | Black |
| **Height** | 5.12 in (13 cm) |
| **Width** | 17.01 in (43.2 cm) |
| **Depth** | 26.89 in (68.3 cm) |
| **Product Weight** | 200.20 lb(US) (90.81 kg) |
| **Mounting Mode** | Not rack-mountable |

## Environmental

| | |
|---|---|
| **Ambient air temperature for operation** | 32…104 °F (0…40 °C) |
| **Operating altitude** | 0...10000 ft |
| **Relative Humidity** | 0…95 % non-condensing |
| **Ambient Air Temperature for Storage** | 5…113 °F (-15…45 °C) |
| **Storage altitude** | 0…50000 ft (0.0000000000…15240.0000000000 m) |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Storage Relative Humidity** | 0…95 % non-condensing |

## Ordering and shipping details

| | |
|---|---|
| **GTIN** | 731304379898 |
| **Country of origin** | MX |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Number of Units in Package 1** | 1 |
| **Package 1 Height** | 16.54 in (42 cm) |
| **Package 1 Width** | 39.37 in (100 cm) |
| **Package 1 Length** | 23.62 in (60 cm) |
| **Package 1 Weight** | 232.10 lb(US) (105.28 kg) |

## Compliance

| | |
|---|---|
| **Compliance** | TAA |

## Contractual warranty

| | |
|---|---|
| **Warranty** | 2 years repair or replace |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Environmental Disclosure | Product Environmental Profile |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | No |
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant with Exemptions |
| REACh Regulation | REACh Declaration |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Circularity Profile | End of Life Information |
| Removable battery | User replaceable |
| Take-back | No |