

Product data sheet

Specifications



Device monitoring and management, Network Management Cards, NMC3 with Environmental Monitoring, secure remote UPS monitoring and management

AP9641

Overview

Lead time Usually in Stock

Main

Range of Product	Network Management Cards
Range Compatibility	Galaxy VM Galaxy VX Symmetra PX Easy UPS 3M Advanced Easy UPS 3-Phase Modular Galaxy PX Smart-UPS Smart-UPS Ultra Smart-UPS Online Smart-UPS Modular Ultra Smart-UPS Battery Systems Back-UPS SX3 Refurbished Smart-UPS
Product or Component Type	Device monitoring and management
Provided Equipment	Temperature Sensor Micro-USB cable Installation manual
Number of input phases	1 3

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Standards	EN 55024 BS EN 55024 EN 61000-4-2 BS EN 61000-4-2 EN 61000-4-3 BS EN 61000-4-3 EN 61000-4-4 BS EN 61000-4-4 EN 61000-4-5 BS EN 61000-4-5 EN 61000-4-6 BS EN 61000-4-6 EN 61000-4-8 BS EN 61000-4-8 EN 61000-4-11 BS EN 61000-4-11 EN 55035 BS EN 55035 EN 62040-2 BS EN 62040-2 EN 61326-2 BS EN 61326-2 ICES-003 class A VCCI class A EN 61000-6-3 BS EN 61000-6-3 EN 55032:class A BS EN 55032:class A
------------------	---

General

Variant option	Environmental monitoring
-----------------------	--------------------------

Physical

Product Weight	0.20 lb(US) (0.09 kg)
Width	4.76 in (12.1 cm)
Height	1.50 in (3.8 cm)
Depth	4.49 in (11.4 cm)

Conformance

Product Certifications	FCC Class A AS/NZS AS/NZS 3548 (C-Tick) Class A FCC part 15 class A GOST UK PSTI
-------------------------------	---

Environmental

Storage Relative Humidity	0...95 %
Relative Humidity	0...95 %
Ambient Air Temperature for Storage	5...149 °F (-15...65 °C)
Ambient air temperature for operation	23...113 °F (-5...45 °C)
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)
Operating altitude	0...10000 ft

Communications & Management

Communication Network Type	10/100/1000BASE-T
Authentication	Radius Lightweight Directory Access Protocol (LDAP)

Communication Port Protocol	HTTP over secure sockets Layer (HTTPS) SSH FTP HTTP SNMP DHCP BOOTP (Bootstrap Protocol) TCP/IP
------------------------------------	---

Ordering and shipping details

GTIN	731304355540
-------------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.05 in (5.200 cm)
Package 1 Width	6.46 in (16.400 cm)
Package 1 Length	9.45 in (24.000 cm)
Package 1 Weight	14.286 oz (405.000 g)

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 123

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant

SCIP Number 1cdb2fed-a06f-4574-913d-8df8e70936b2

REACH Regulation [REACH Declaration](#)

Energy efficiency

Optimized Energy Efficiency Energy efficient product

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Removable battery Yes

Take-back Yes