Product data sheet

Specifications



APC Rack PDU 9000 Switched, ZeroU, 16A, 100-240V, (21) C13/ C15 & (3) C19/C21, Japan

APDU9959J

Overview

Lead time	Usually in Stock

Main

Color	Black
Product or Component Type	PDU
PDU Type	Switched
Provided Equipment	Installation guide Rack Mounting brackets Safety guide

Complementary

Input Voltage	200 V
Height	70.75 in (179.7 cm)
Width	2.17 in (5.5 cm)
Output Voltage	200 V
Depth	1.81 in (4.6 cm)
Product Weight	12.24 lb(US) (5.55 kg)
Mounting Location	Side
Mounting preference	No preference
Input Plug Type	IEC 60320 L6-20P
Mounting Mode	Not rack-mountable
Rack units	0U
USB compatible	No
Mounting position	Vertical
Communication Port Protocol	SNMP Redfish
Line Rated Current	16 A
Acceptable Input Voltage	100…240 V
Input current limits	20 A
Load Capacity	3300 VA
Input Frequency	50/60 Hz
Outlet type and quantity	21C13/C15 3C19/C21

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Communication Network Type	10/100/1000BASE-T

Environment

Product Certifications	FCC part 15 class A PSE
Ambient air temperature for operation	23…140 °F (-5…60 °C)
Relative Humidity	5…95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13…149 °F (-25…65 °C)
Storage Relative Humidity	5…95 %
Storage altitude	0…50000 ft (0.0000000000…15240.0000000000 m)

Ordering and shipping details

GTIN	731304412922

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	78.82 in (200.2 cm)
Package 1 Width	4.49 in (11.4 cm)
Package 1 Length	6.50 in (16.5 cm)
Package 1 Weight	17.33 lb(US) (7.86 kg)

Contractual warranty

Warranty	3 years repair or replace

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	31346aed-552c-4a16-81d9-e683a383b6da
REACh Regulation	REACh Declaration

Use Again

Repack and remanufacture

Circularity Profile	End of Life Information
Removable battery	Yes
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative



