

Product data sheet

Specifications



Rack PDU, Switched, ZeroU, 12.5kW, 208V, (21)C13 & (3)C19; 3ft input Cord

AP7968B

Overview

Lead time Usually in Stock

Main

Color Black

Product or Component Type PDU

PDU Type Switched

Cord length 3 ft (0.9 m)

Number of cables 1

Provided Equipment
Cord retention bracket(s)
Documentation CD
Installation guide
Rack Mounting brackets
RS-232 configuration cable
Toolless Mounting Kit

Complementary

Input Voltage 208 V 3 phase

Height 70.00 in (177.8 cm)

Width 2.20 in (5.6 cm)

Output Voltage 208 V

Depth 3.50 in (8.9 cm)

Product Weight 17.81 lb(US) (8.08 kg)

Mounting Location Side

Mounting preference No preference

Mounting Mode Rack-mounted

Rack units 0U

Mounting position Vertical

Max line current 35 A

Input current limits 35 A

Load Capacity 12500 VA

Input Frequency 50/60 Hz

Number of input connectors 1 CS8365

Outlet type and quantity
21 IEC 60320 C13
3 IEC 60320 C19

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

Product Certifications	cUL Listed CSA Industry Canada UL Listed
Standards	FCC Part 15 class A ICES-003 UL 60950
Ambient air temperature for operation	23...113 °F (-5...45 °C)
Relative Humidity	5...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)

Ordering and shipping details

GTIN	731304331650
Country of origin	IN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	82.99 in (210.8 cm)
Package 1 Width	5.00 in (12.7 cm)
Package 1 Length	5.98 in (15.2 cm)
Package 1 Weight	24.34 lb(US) (11.04 kg)

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 3252

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number 1cdb2fed-a06f-4574-913d-8df8e70936b2

REACH Regulation [REACH Declaration](#)

Halogen content performance Product contains halogen above thresholds

Energy efficiency

Optimized Energy Efficiency Energy efficient product

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Removable battery Yes

Take-back Yes

Image of product / Alternate images

Alternative









