

CW-31 Petite Wall Wash **STANDARD**




PROJECT
CATALOG #
TYPE
NOTES

Featuring an elegant design with an antique bronze finish, the Cora CW-31 Petite Wall Wash is the perfect addition to lighting projects with modest budgets. Combining a corrosion-resistant brass construction with black oxide stainless steel hardware, this directional flood and wall wash fixture is especially well-suited for coastal regions. Designed to outlast any landscape, the CW-31's minimal size makes it the perfect choice for projects that may require a smaller fixture footprint or soft, filtered light.

Quick Facts

- 10' (3 m) lead
- Provides soft, filtered light — great for tying in focal points
- Solid brass construction and black oxide stainless steel hardware deliver strong corrosion resistance
- Antique bronze finish provides increased durability and elegant look
- Fully potted on the inside to prevent water intrusion in any orientation
- Directional flood and wall wash fixture offers added design flexibility



CW-31 Petite Wall Wash SPECIFICATIONS

Output	LED-35 W
Total Lamp Lumens (lm)	66
Input Voltage VAC/VDC	10 to 15
Power Consumption (VA)	2.6
Efficacy (Lm/W)	41
Color Rendering Index (CRI)	80+
Maximum Candela (cd)	39
Minimum Rated Life (L70)	33,000 hrs

CW-31 Petite Wall Wash SPECIFICATIONS

Standard T3/G4 lamp FX Luminaire

FX Luminaire is an industry-leading manufacturer of landscape and architectural lighting products with a focus on the advancement of LED technology and digital lighting control with zoning, dimming, and color adjustment capabilities. We offer a full spectrum of specification-driven lighting fixtures that can be utilized to create elegant, cutting-edge landscape lighting systems for commercial or residential applications. Our products are available exclusively via our extensive professional distributor network.

Materials

Brass fixture with black oxide stainless steel hardware

Optics

Internal reflector

Threads

½"-14 NPSM

Dimming

Primary: Consult transformer specifications. Secondary: Luxor® control (with ZD lamp) or a trailing-edge (reverse phase-cut) dimmer

Adjustability

Compress-and-lock features prevent slip after installation. Offers 9° increments of adjustability over 220° of vertical alignment.

Finish

Antique Bronze finish sealed with a clear TGIC powder-coat layer

Hardware

Black oxide stainless steel adjustment screw (Phillips). Includes 7" ABS slotted installation spike.

Wiring

18 AWG (1 mm); SPT-1W; 220°F (105°C); 300 V; 10' (3 m) length, measured from the light aperture

Sockets

Socket contains MoistureBlock™ technology, preventing moisture from wicking up into sealed areas of the fixture.

Glare Control

20° angled shield

Weight

1.9 lb (0.7 kg)

Lens

OptiClear™ tempered glass for exceptional optical purity and load strength

Ambient Operating Temperature

0°F to 140°F (-18°C to 60°C)

Power Consumption

2.6 VA

Sustainability

Innovation meets conservation in the design and manufacturing of our products. Where we can, we use recycled materials while maintaining superior functionality. Our LED products provide high quality light at optimal energy efficiency, lifespan, and durability.

Installation Requirements

Must be installed in the upward direction only

Lens Transparency

Frosted

Manufacturing

ISO 9001:2015 certified facility

Warranty

Fixture: 10-year limited
Included Lamp: 5-year limited

Listings



CW-31 Petite Wall Wash ORDERING INFORMATION

Fixture

Lamp

Mounting

Finish

CW-31

LED35W

[default]

Super Slot Spike included

AB

Antique Bronze



FIXTURE CONFIGURATION: *CW31*-LED35W-AB

CW-31 LED35W - Illuminance at a Distance

Distance	Center Beam fc	Beam Width	
Feet (Meters)	Foot-Candles (Lux)	Vertical : 76 °	Horizontal : 86 °
20' (6 m)	0.1 fc (1 lx)	31' (9 m)	38' (12 m)
16' (5 m)	0.2 fc (2 lx)	25' (8m)	30' (9 m)
12' (4 m)	0.3 fc (3 lx)	19' (6m)	23' (7 m)
8' (2 m)	0.6 fc (6 lx)	13' (4 m)	15' (5 m)
4' (1 m)	2.4 fc (26 lx)	6' (2 m)	8' (2 m)

CW-31 Petite Wall Wash ORDERING INFORMATION

MOUNTING OPTIONS: Specify Separately

Mounts	Catalog No.		Mounts	Catalog No.	
Long Slot Spike	250015840000		Three-Prong Spike	250020020000	
Lock Ring	250030410000SP		Super Slot Spike	753900	
Bracket Mount	BM-050-XX*		CE Certified Spike	eKitSpike	
Gutter Mount	GM-SS		Ground Mount with 1/2" Thread	GM-XX*	
Line Mount	LNМ		Mini J-Box for 1/2" Thread	MJB-050-XX*	
ProAim® Ratcheting Spike	PARS		Post Mount	PM-XX*	
Super J-Box Spike	SJ-XX*		TreeBox® Mount with 1/2" Thread	TB-XX*	
Tree Ring	TR-YY*-6P-XX*		VersaBox® Mount with 1/2" Thread	VB-050-XX*	
Variable Height Riser for Up Lights	VHR-UL		Single-Gang Wall Plate with 1/2" Thread	WP-1G-050-XX*	
Round Wall Plate with 1/2" Thread	WP-RD-050-XX*		1.0" (25 mm) Copper Riser for GT Path Light	YY*-R-GT-XX*	

CW-31 Petite Wall Wash ORDERING INFORMATION

POWER OPTIONS: Specify Separately

Power	Catalog No.		Power	Catalog No.	
Low-Voltage Dimmer	DIM-LV		DX Transformer 150 W Matte Grey	DX150M	
DX Transformer 150 W Stainless Steel	DX150SS		DX 300 W Matte Grey	DX300M	
DX Transformer 300 W Stainless Steel	DX300SS		EX Transformer 150 W Matte Grey	EX150M	
EX Transformer 150 W Stainless Steel	EX150SS		Luxor Cube - Low voltage	LCM-LV	
Mini Plug-In Transformer, 30 W	MT-30W		Plug-In Transformer, 6 W	MT-6W	
PX Transformer 300 W	PX300SS		PX Transformer 600 W	PX600SS	
PX Transformer 900 W	PX900SS		Step-Down Transformer, Dimmable (120 V to 12 V)	ST-120-DIM	
Step-Down Transformer, UV (120/277 V to 12 V)	ST-UV		Lighting Fixture Surge Module	SURGE-MOD	

CW-31 Petite Wall Wash ORDERING INFORMATION

SPLICING OPTIONS: Specify Separately

Splicing	Catalog No.		Splicing	Catalog No.	
Brass Lug Wire Connectors, 2-pack	WCHSBS2		Brass Lug Wire Connectors, 50-item bulk pack	WCHSBS50	
Heat Shrink Wire Connectors, 20-pack, Medium	WCHSMD20		Heat Shrink Wire Connectors, 20-pack, Small	WCHSSM20	
Ratcheting Crimper Tool	WCHSTOOL				