



Product: [1800F](#) 

Digital Microphone Cable, 1 Pr #24 Str BC, 95% TC French Braid, PVC Jkt, CL2R, Flexible

Product Description

Digital Microphone Cable, 1 Pair 24 AWG (42x40) Bare Copper, PE insulation, 95% Tinned Copper French Braid Shield, Matte PVC jacket, CL2R-rated, Flexible

Technical Specifications

Product Overview

Suitable Applications:	Digital microphone; Flexible interconnect cable for digital audio
------------------------	---

Construction Details

Conductor

Element	No. of Elements	Size	Stranding	Material
Pair(s)	1	24 AWG	42x40	BC - Bare Copper

Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code	Notes
Pair(s)	PE - Polyethylene (Foam)	0.017 in (0.43 mm)	0.058 in (1.5 mm)	Red & Black	HDPE

Outer Shield

Shield Type	Material	Coverage	Drainwire Type	Notes
French Braid	Tinned Copper (TC)	95%	26 AWG (30x40) BC	Paper tape under braid with drain over tape

Outer Jacket

Material	Nom. Thickness	Nom. Diameter
PVC - Polyvinyl Chloride	0.037 in (0.94 mm)	0.211 in (5.36 mm)

Overall Cable Diameter (Nominal):	0.211 in (5.36 mm)
-----------------------------------	--------------------

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Nom. Characteristic Impedance	Nom. Inductance	Nom. Velocity of Prop.	Max. Current
Pair(s)	23.7 Ohm/1000ft	12 pF/ft (39 pF/m)	26 pF/ft (85 pF/m)	110 Ohm	0.18 µH/ft (0.59 µH/m)	76%	3.8 Amps per conductor @ 30°C

Nom Outer Shield DCR@Cond DCR1-cnrv:	6.42 Ohm/1000ft (21.1 Ohm/km)
--------------------------------------	-------------------------------

High Frequency (Nominal/Typical)

Nom. Insertion Loss (Attenuation)
0.46 dB/100ft
0.67 dB/100ft
0.7 dB/100ft
0.83 dB/100ft
1.04 dB/100ft
1.09 dB/100ft
1.3 dB/100ft
1.66 dB/100ft
1.75 dB/100ft

2.23 dB/100ft
2.89 dB/100ft
3.07 dB/100ft
3.71 dB/100ft
4.53 dB/100ft
4.78 dB/100ft
7.11 dB/100ft

Voltage

Voltage Rating
100 V

Mechanical Characteristics

Temperature

UL Temperature	Operating
60°C	-20°C to +60°C

Bend Radius

Stationary Min.	Installation Min.
2.1 in (53 mm)	2.1 in (53 mm)

Max. Pull Tension:	40 lbs (18 kg)
Bulk Cable Weight:	23 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor - Riser, Indoor
Flammability / Reaction to Fire:	UL 1666 Riser
NEC / UL Compliance:	Article 725, CL2R
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Other Standard Compliance(s):	AES/EBU

History

Update and Revision:	Revision Number: 0.523 Revision Date: 09-07-2025
----------------------	--

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC	Footnote
1800F B59500	Black, Matte	Reel	500 ft	612825122845	C
1800F B591000	Black, Matte	Reel	1,000 ft	612825122838	C
1800F B59U1000	Black, Matte	UnReel	1,000 ft	612825122821	
1800F B5910000	Black, Matte	Reel	10,000 ft	612825429944	
1800F G7XU1000	Blue, Matte	UnReel	1,000 ft	612825122876	
1800F U90U1000	Gray, Matte	UnReel	1,000 ft	612825122890	
1800F G7WU1000	Green, Matte	UnReel	1,000 ft	612825122869	
1800F G7VU1000	Red, Matte	UnReel	1,000 ft	612825122852	
1800F Z4BU1000	Violet Z4B	UnReel	1,000 ft	612825122906	
1800F G8MU1000	Yellow, Matte	UnReel	1,000 ft	612825122883	

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.