

# Product datasheet

Specifications



## APC IT Power Distribution Module 3 Pole 5 Wire 16A IEC309 440cm

PDM3516IEC-440

### Overview

**Presentation** Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.

**Lead time** Usually Ships within 3 Weeks

### Main

**Main Input Voltage** 400 V 3 phases

**Main Output Voltage** 230 V  
400 V 3 phases

**Provided equipment** Installation guide

### Physical

**Colour** Grey

**Height** 15.2 cm

**Width** 43.2 cm

**Depth** 40.6 cm

**Net weight** 2.39 kg

### Input

**Network frequency** 50 Hz

**Max line current** 16 A

### Output

**Max current draw** 16 A

**Number of power socket outlets** 1 IEC 309 16 A

### Conformance

**product certifications** CE  
VDE

### Packing Units

**Unit Type of Package 1** PCE

**Number of Units in Package 1** 1

**Package 1 Height** 15.2 cm

**Package 1 Width** 40.6 cm

---

Package 1 Length	43.2 cm
------------------	---------

---

Package 1 Weight	3.3 kg
------------------	--------

## Contractual warranty

---

Warranty	1 year repair or replace
----------	--------------------------

## Sustainability

**Green Premium™** label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more about Green Premium >](#)



Take-back   Transparency

## Resource performance

✓ Take-Back Program Available

---

## Well-being performance

✓ Mercury Free

---

**Reach Regulation**

[REACH Declaration](#)

---

**Eu Rohs Directive**

Under investigation

---

**Environmental Disclosure**

[Product Environmental Profile](#)

---

**Circularity Profile**

[End of Life Information](#)

---

Image of product / Alternate images

Alternative

---



