

Product data sheet

Specifications



UPS Network Management Card 2 w/ Environmental Monitoring, Out of Band Access and Modbus

AP9635

! To be discontinued

! To be discontinued on: Jul 15, 2025

! To be end-of-service on: Aug 15, 2025

Product availability: Stock - Normally stocked in distribution facility

Overview

Lead time Usually in Stock

Main

Provided Equipment CD with software
Temperature Sensor
User Manual

Physical

Height 1.50 in (3.81 cm)

Width 4.76 in (12.1 cm)

Depth 4.25 in (10.8 cm)

Product Weight 0.31 lb(US) (0.14 kg)

Mounting preference No preference

Mounting Mode Not rack-mountable

Conformance

Standards EN 55022 Class A
FCC Part 15 class A
ICES-003

Product Certifications AS/NZS 3548 (C-Tick) Class A
GOST
VCCI Class A

Environmental

Ambient air temperature for operation 23...113 °F (-5...45 °C)

Operating altitude 0...10000 ft

Relative Humidity 0...95 % non-condensing

Ambient Air Temperature for Storage 5...149 °F (-15...65 °C)

Storage altitude 0...50000 ft (0.0000000000...15240.0000000000 m)

Storage Relative Humidity 0...95 %

Communications & Management

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Authentication	Radius
----------------	--------

Ordering and shipping details

Category	80230-IG SEBA TO SEUSA
Discount Schedule	BMS1
GTIN	731304267768
Returnability	No
Country of origin	PH

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.97 in (5.000 cm)
Package 1 Width	9.25 in (23.500 cm)
Package 1 Length	6.38 in (16.200 cm)
Package 1 Weight	20.670 oz (586.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	3
Package 2 Height	11.81 in (30.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	4.409 lb(US) (2.000 kg)

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 192

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Pro-active compliance (Product out of EU RoHS legal scope)

SCIP Number 1cdb2fed-a06f-4574-913d-8df8e70936b2

REACH Regulation [REACH Declaration](#)

Halogen content performance Product contains halogen above thresholds

Energy efficiency

Optimized Energy Efficiency Energy efficient product

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back Yes

Image of product / Alternate images

Alternative

The screenshot shows the 'Home' page of the Schneider Electric UPS Network Management Card 2. The page features a green navigation bar with links for Home, Status, Control, Configuration, Trends, Logs, and About. The main content area includes a 'Home' section with the model 'SmartUPS X 1500' and location '1st Floor LAB'. A status indicator shows 'No Alarms Present' with a sub-message 'UPS is Online in Green Mode'. Below this is a 'Recent Device Events' table with one entry: '19/02/2025 11:27:35 UPS: Restore the local network management interface to UPS system (admin)'. A 'More Events' button is located to the right of the table. At the bottom, there are links for 'Knowledge Base', 'Schneider Electric Product Center', and 'Schneider Electric Downloads', along with copyright information: '© 2025, Schneider Electric. All rights reserved. 09-1000-1100000-001239'.

The screenshot shows the 'UPS Status' page of the Schneider Electric UPS Network Management Card 2. The page features a green navigation bar with links for Home, Status, Control, Configuration, Trends, Logs, and About. The main content area is titled 'UPS Status' and displays the following information for the 'Smart-UPS X 1500':
- **Last Battery Transfer:** None
- **Battery Temperature:** 35.2°C
- **Runtime Remaining:** 2hr 13min 57sec
UPS Input:
- **Input Voltage:** 122.1 VAC @ 50.0 Hz
UPS Output:
- **Output Voltage:** 122.1 VAC @ 50.0 Hz
- **Output VA:** 0.0 %
- **Output Efficiency:** load too low
- **Load Current:** 0.2 Arms
- **Output Watts:** 0.0 W
- **Output Energy Usage:** 0.00 kWh



