Product data sheet

Specifications



APC Smart-UPS SRT 192V 5kVA and 6kVA Battery Pack [TAA]

SRT192BPUS

Overview

Lead time	Usually in Stock

Main

Product or Component Type	Battery
Battery Type	Lead-Acid battery
Provided Equipment	Documentation CD Installation guide Warranty card
Range of Product	Smart-UPS Battery Systems

Batteries & Runtime

Battery Slots Empty	0
Included Battery Modules	0
Device mounting	Stand alone battery stack
Battery Voltage	192V
RBC Quantity	2
Replacement battery	APCRBC140

Physical

Color	Black
Height	17.01 in (43.2 cm)
Width	5.12 in (13 cm)
Depth	26.89 in (68.3 cm)
Product Weight	200.20 lb(US) (90.81 kg)
Mounting Mode	Not rack-mountable

Environmental

Ambient air temperature for operation	32…104 °F (0…40 °C)
Operating altitude	0...10000 ft
Relative Humidity	0…95 % non-condensing
Ambient Air Temperature for Storage	5…113 °F (-15…45 °C)
Storage altitude	0…15000 ft (0.0000000000…4572.0000000000 m)
Storage Relative Humidity	0…95 % non-condensing

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ordering and shipping details

GTIN	731304379874
Country of origin	PH

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.54 in (42 cm)
Package 1 Width	39.37 in (100 cm)
Package 1 Length	23.62 in (60 cm)
Package 1 Weight	223.31 lb(US) (101.29 kg)

Compliance

Compliance	TAA

Contractual warranty

Warranty	2 years repair or replace

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	464
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration

Use Again

Repack and remanufacture

Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	No