Specifications

Eaton EMI303-10



Catalog Number: EMI303-10

Eaton Metered Input rack PDU, 0U, L15-30P input, 8.64 kW max, 200-240V, 24A, 10 ft cord, Three-phase, Outlets: (30) C13 Outlet grip, (6) C19 Outlet grip

General specifications

Product Name
Eaton metered input PDU

Catalog Number
EMI303-10

UPC
786685885049

Product Length/Depth
66.5 in

Product Height
2.1 in

Product Width
2.05 in

Product Weight
16.6 lb

Warranty
3 year

Compliances
Contact Manufacturer
TAA Compliant

Certifications
UL Listed

Product specifications

Form factor
0U (Vertical)

Outlet control
No

Phase
Three-phase

Wattage
8.64 kW max

Amperage Rating
24A

Input voltage
200-240V

Input connection
L15-30P

Outlets
(30) C13 Outlet grip, (6) C19 Outlet grip

Cord length
10 ft

Frequency rating
50-60 Hz

Ethernet interface
Yes

Serial interface
RS-232

Operating Temperature
0° to 60°C (32° to 140°F)

Resources

Certification reports
Eaton RoHS Declaration of Conformity: ePDU G3

Drawings
Eaton ePDU G3 Metered Input EMI303-10 technical drawing

Manuals and user guides
Eaton ePDU G3 installation and connectivity quick start guide

Eaton ePDU G3 EMP installation and connection quick start guide

Eaton ePDU G3 operations manual

Eaton ePDU G3 instruction set - system objects

Service and troubleshooting
EMI303-10 eNMC replacement configuration file

Specifications and datasheets
Eaton Specification Sheet - EMI303-10



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia