

Product data sheet

Specifications



APC NetShelter Power Cord, IEC C19 to C14, 2.0m



AP9878

Product availability: Stock - Normally stocked in distribution facility

Overview

Lead time Usually in Stock

Main

| | |
|---------------------------|----------------|
| Product or Component Type | Power cord |
| Input Connection Type | IEC 60320 C14 |
| Cable length | 6.5 ft (2.0 m) |
| Number of cables | 1 |

Physical

| | |
|---------------------|-----------------------|
| Color | Black |
| Product Weight | 0.62 lb(US) (0.28 kg) |
| Mounting preference | No preference |
| Mounting Mode | Not rack-mountable |

Input

Max line current 10 A

Output

| | |
|--------------------------------------|-----------------|
| Maximum Total Current Draw per Phase | 10 A |
| Number of power socket outlets | 1 IEC 60320 C19 |

Ordering and shipping details

| | |
|-------------------|---------------------------|
| Category | 11309-APC RESALE PRODUCTS |
| Discount Schedule | APC1 |
| GTIN | 731304198772 |
| Returnability | No |
| Country of origin | US |

Packing Units

| | |
|------------------------------|--------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 12.01 in (30.5 cm) |
| Package 1 Width | 4.02 in (10.2 cm) |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| | |
|-------------------------------------|-------------------------|
| Package 1 Length | 4.02 in (10.2 cm) |
| Package 1 Weight | 0.791 lb(US) (0.359 kg) |
| Unit Type of Package 2 | CAR |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 9.25 in (23.5 cm) |
| Package 2 Width | 13.19 in (33.5 cm) |
| Package 2 Length | 20.87 in (53 cm) |
| Package 2 Weight | 9.5 lb(US) (4.3 kg) |
| Unit Type of Package 3 | PAL |
| Number of Units in Package 3 | 10 |
| Package 3 Height | 56.69 in (143.99 cm) |
| Package 3 Width | 39.37 in (100 cm) |
| Package 3 Length | 47.24 in (120 cm) |
| Package 3 Weight | 9.5 lb(US) (4.3 kg) |

Contractual warranty

| | |
|-----------------|---------------------------|
| Warranty | 2 years repair or replace |
|-----------------|---------------------------|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) **88**

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard **No**

Packaging without single use plastic **No**

[EU RoHS Directive](#) **Compliant**

SCIP Number **1cdb2fed-a06f-4574-913d-8df8e70936b2**

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov**

Halogen content performance **Product contains halogen above thresholds**

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back **Yes**

WEEE  **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**

Image of product / Alternate images

Alternative

