



Product: [FXU Frame OM4 12P](#)

FX Ultra Frame OM4 12 Ports

Product Description

FX Ultra Frame OM4 12 Ports. Available in several fiber connector types.

Technical Specifications

Product Overview

Environmental Space:	Indoor
Suitable Applications:	FiberExpress Solutions, Backbone, Telecommunications Room, Main Distribution Room, Data Centers

Construction

Fiber Cable Construction

Fiber Type	OM4
Weight:	0.25 lbs
Height:	1.5 in
Width:	4.46 in
Depth:	2.2 in

Temperature Range

Operating Temp Range:	-10 to 60°C
Storage Temp Range:	-10 to 75°C

Product Material

Materials

Description	Material	Color
Frame	Plastic - UL94V-0	Black
Front Connector Body	Plastic - UL94V-0	Erika Violet

Standards

MII Order #39 (China RoHS):	EUP 50
-----------------------------	--------

Part Number

Included Parts:	Dust Caps
Related Parts:	FiberExpress Ultra Patch panels, Pre-terminated MPO low loss cable assemblies

Variants

Item #	Color	Connector Type	Port Count
FF4U12MP	Erika Violet	MPO Up/Down	12 Port
FF4U12LKY	Erika Violet	LC Keyed Yellow	12 Port
FF4U12LKW	Erika Violet	LC Keyed White	12 Port
FF4U12LKV	Erika Violet	LC Keyed Violet	12 Port
FF4U12LKS	Erika Violet	LC Keyed Gray	12 Port
FF4U12LKR	Erika Violet	LC Keyed Red	12 Port

FF4U12LKP	Erika Violet	LC Keyed Rose	12 Port
FF4U12LKO	Erika Violet	LC Keyed Orange	12 Port
FF4U12LKN	Erika Violet	LC Keyed Black	12 Port
FF4U12LKM	Erika Violet	LC Keyed Brown	12 Port
FF4U12LKG	Erika Violet	LC Keyed Green	12 Port
FF4U12LKB	Erika Violet	LC Keyed Blue	12 Port
FF4U12LKA	Erika Violet	LC Keyed Aqua	12 Port
FF4U12SC	Erika Violet	SC	12 Port

Product Notes

Packaging:	Individually packaged in a plastic shell, Shipped in cardboard box (60/box)
------------	---

History

Update and Revision:	Revision Number: 0.106 Revision Date: 06-30-2021
----------------------	--

© 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.