

# Product data sheet

Specifications

## APC IT Power Distribution Module 3 Pole 5 Wire 20A L21-20 920cm



PDM3520L2120-920

### Overview

|                     |  |
|---------------------|--|
| <b>Presentation</b> | Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time. |
| <b>Lead time</b>    | Usually Ships within 3 Weeks   |

### Main

|                            |                    |
|----------------------------|--------------------|
| <b>Main Input Voltage</b>  | 208 V 3 phase      |
| <b>Main Output Voltage</b> | 120 V              |
| <b>Provided Equipment</b>  | Installation guide |

### Physical

|                   |                           |
|-------------------|---------------------------|
| <b>Color</b>      | Black                     |
| <b>Height</b>     | 5.0000000000 in (12.7 cm) |
| <b>Width</b>      | 17.5 in (44.5 cm)         |
| <b>Depth</b>      | 16.0 in (40.6 cm)         |
| <b>Net Weight</b> | 13.03 lb(US) (5.91 kg)    |

### Input

|                            |             |
|----------------------------|-------------|
| <b>Input Frequency</b>     | 60 Hz       |
| <b>Permissible voltage</b> | 200...240 V |
| <b>Max line current</b>    | 20 A        |

### Output

|   |               |
|---|---------------|
| <b>Maximum Total Current Draw per Phase</b> | 20 A          |
| <b>Number of power socket outlets</b>       | 1 NEMA L21-20 |

### Conformance

|                               |           |
|-------------------------------|-----------|
| <b>Product Certifications</b> | UL Listed |
|-------------------------------|-----------|

### Ordering and shipping details

|             |              |
|-------------|--------------|
| <b>GTIN</b> | 731304282204 |
|-------------|--------------|

### Packing Units

|                               |     |
|-------------------------------|-----|
| <b>Unit Type of Package 1</b> | PCE |
|-------------------------------|-----|

---

|                                     |                           |
|-------------------------------------|---------------------------|
| <b>Number of Units in Package 1</b> | 1                         |
| <b>Package 1 Height</b>             | 5.0000000000 in (12.7 cm) |
| <b>Package 1 Width</b>              | 16.0 in (40.6 cm)         |
| <b>Package 1 Length</b>             | 17.5 in (44.5 cm)         |
| <b>Package 1 Weight</b>             | 14.22 lb(US) (6.45 kg)    |

---

## **Contractual warranty**

---

|                 |                          |
|-----------------|--------------------------|
| <b>Warranty</b> | 1 year repair or replace |
|-----------------|--------------------------|

## Sustainability

**Green Premium™** label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more about Green Premium >](#)



Take-back   Transparency

## Resource performance

Take-Back Program Available

---

## Well-being performance

Mercury Free

---

**Reach Regulation**

[REACH Declaration](#)

---

**Eu Rohs Directive**

Under investigation

---

**Environmental Disclosure**

[Product Environmental Profile](#)

---

**Circularity Profile**

[End of Life Information](#)

---