Product data sheet

Specifications



APC Smart-UPS Ultra Step-Down Transformer, 5kVA, rackmount, 2U, 12x NEMA 5-20R outlets

SRTL5KRMTF

Overview

Lead time	Usually in Stock

Main

Main Input Voltage	208 V
Product or Component Type	Transformer
Main Output Voltage	120 V
Kw Rating	5000 W
Rated power in VA	5 kVA
Input Connection Type	NEMA L6-30P
Number of rack unit	2U
Number of cables	1
Provided Equipment	Mounting Hardware
Range of Product	Smart-UPS Ultra

Physical

Color	Black
Height	8.35 in (21.2 cm)
Width	23.31 in (59.2 cm)
Depth	30.71 in (78 cm)
Product Weight	101.4 lb(US) (46 kg)
Mounting Location	Front
Mounting preference	No preference
Mounting Mode	Rack-mounted
Mounting position	Horizontal

Input

Max line current	24 A
Input current limits	30 A
Load Capacity	5000 VA
Input Frequency	50/60 Hz

Output

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Maximum Total Current Draw per Phase	24 A
Number of power socket outlets	12
Number of power socket outlets	12 NEMA 5-20R

Conformance

Product Certifications	CSA
Standards	UL 1778

Environmental

Ambient air temperature for operation	32…104 °F (0…40 °C)
Relative Humidity	0…95 % non-condensing
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5…113 °F (-15…45 °C)
Storage Relative Humidity	0…95 % non-condensing
Storage altitude	0…50000 ft (0.0000000000…15240.0000000000 m)

Ordering and shipping details

GTIN	731304437055

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.00 in (25.4 cm)
Package 1 Width	37.48 in (95.2 cm)
Package 1 Length	24.49 in (62.2 cm)
Package 1 Weight	110.01 lb(US) (49.9 kg)

Contractual warranty

Warranty	5 years repair or replace

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	5ee38369-4dfb-4636-ab65-b08aa3242891
REACh Regulation	REACh Declaration

Use Again

Repack and remanufacture

Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

