Product data sheet

Specifications



APC Smart-UPS On-Line, 10kVA/ 10kW, Tower, 208V, 16x 5-20R+4x L6-20R+6x L6-30R+2x L14-30R NEMA, NMC+SmartSlot,W/2 transformer 208V to 120V,W/O rail kit

SRT10KXLT-5KTF2

Overview

Lead time	Usually in Stock

Main

Main Input Voltage	208 V
Product or Component Type	Uninterruptible power supply (UPS)
Other Input Voltage	240 V
Main Output Voltage	120 V 208 V
Other Output Voltage	240 V
Kw Rating	10000 W
Rated power in VA	10000 VA
output connection type	16 NEMA 5-20R 4 NEMA L6-20R 6 NEMA L6-30R 2 NEMA L14-30R
Output connector type	Hard Wire 3-wire (2PH + G) 1
Provided equipment	CD with software Documentation CD Installation guide Temperature Probe USB cable Warranty card Web/SNMP Management Card
Range of Product	Smart-UPS On-Line

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Battery Type	Lead-Acid battery
Battery Voltage	+/-192 V (split battery referenced to neutral)
Extendable Run Time	1
Included Battery Modules	0
Typical recharge time	1.5 h
RBC Quantity	2

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Battery life	3…5 year(s)
Replacement battery	APCRBC140
Battery Charge Power (Watts)	1191 W rated

General

Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	High density
Redundant	No
Topology	Double Conversion Online

Physical

color	Black
Height	17.01 in (43.2 cm)
Width	20.55 in (52.2 cm)
Depth	28.15 in (71.5 cm)
Product Weight	496.00 lb(US) (224.98 kg)
Mounting Location	Front
Mounting preference	No preference
Mounting Mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes
Mounting position	Vertical

Input

Efficiency at full load	100...275 V adjustable (half load)
Number of input connectors	1 Hard Wire 3-wire (2PH + G)
Input Frequency	40 - 70 Hz auto-sensing

Output

Bypass type	Internal Bypass (Automatic and Manual)
Crest factor	3 : 1
Harmonic distortion	Less than 2%
Maximum configurable power in VA	10000 VA
Max Configurable Power (Watts)	10000 W
Waveform Type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Conformance

Product Certifications	ENERGY STAR V2.0 (USA) FCC part 15 class A UL 1778

Environmental

Acoustic level	55 dBA
Online Thermal Dissipation	2490 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	32…104 °F (0…40 °C)
Ambient Air Temperature for Storage	5…113 °F (-15…45 °C)
Storage altitude	0…50000 ft (0.0000000000…15240.0000000000 m)
IP degree of protection	IP20
Relative Humidity	0…95 % non-condensing
Storage Relative Humidity	0…95 % non-condensing

Communications & Management

Emergency Power Off (EPO)	Yes
Free slots	1
Pre-Installed SmartSlot™ Cards	Network management card 3 with environmental monitoring
Alarm	Audible and visible alarms : prioritized by severity

Surge Protection and Filtering

Surge energy rating	480 J

Ordering and shipping details

GTIN	731304732921

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	49.09 in (124.7 cm)
Package 1 Width	39.37 in (100 cm)
Package 1 Length	23.74 in (60.3 cm)
Package 1 Weight	564.80 lb(US) (256.19 kg)

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	24583
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Energy efficiency

Optimized Energy Efficiency	Energy efficient product
ENERGY STAR®	ENERGY STAR UPS V2.0 (USA)

Use Again

Repack and remanufacture

Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes

Image of product / Alternate images

Alternative



