

Product data sheet

Specifications



Maintenance Bypass Panel, single unit, 20-60kW 400V wallmount, for Galaxy VS and Easy UPS 3S

GVSBPSU20K60H

Overview

Presentation	Maintenance bypass panel for complete isolation of the UPS during service operations.
Lead time	Usually Ships within 2 Weeks

Main

Product or Component Type	Panel
---------------------------	-------

Physical

Height	23.6 in (60 cm)
Width	21.7 in (55 cm)
Depth	8.7 in (22 cm)
Net Weight	55.1 lb(US) (25 kg)

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Ambient Air Temperature for Storage	-13...131 °F (-25...55 °C)

Ordering and shipping details

GTIN	731304342571
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	18.110 in (46.000 cm)
Package 1 Width	28.740 in (73.000 cm)
Package 1 Length	31.496 in (80.000 cm)
Package 1 Weight	94.799 lb(US) (43.000 kg)

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

Energy Efficient Product

Take-Back Program Available

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)

Image of product / Alternate images

Alternative



