Product datasheet

Specifications



APC IT Power Distribution Module 3 Pole 5 Wire 32A IEC309 200cm

PDM3532IEC-200

Overview

Presentation	Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.
Lead time	Usually Ships within 3 Weeks

Main

Main Input Voltage	400 V 3 phases
Main Output Voltage	230 V 400 V 3 phases
Provided equipment	Installation guide

Physical

Colour	Grey
Height	15.2 cm
Width	43.2 cm
Depth	40.6 cm
Net weight	2.09 kg

Input

Network frequency	50 Hz
Max line current	32 A

Output

Max current draw	32 A
Number of power socket outlets	1 IEC 309 32 A

Conformance

product certifications	CE VDE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.2 cm
Package 1 Width	40.6 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Length	43.2 cm
Package 1 Weight	3 kg

Contractual warranty

Warranty	1 year repair or replace

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Take-back



Transparency

Resource performance

- Take-Back Program Available

Well-being performance

- Mercury Free

Reach Regulation	REACh Declaration
Eu Rohs Directive	Under investigation
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Image of product / Alternate images

Alternative





